



Mac OS X Server System Imaging and Software Update Administration

For Version 10.6 Snow Leopard

© 2009 Apple Inc. All rights reserved.
The owner or authorized user of a valid copy of Mac OS X Server software may reproduce this publication for the purpose of learning to use such software. No part of this publication may be reproduced or transmitted for commercial purposes, such as selling copies of this publication or for providing paid-for support services.

Every effort has been made to ensure that the information in this manual is accurate. Apple Inc., is not responsible for printing or clerical errors.

Apple

1 Infinite Loop
Cupertino CA 95014
www.apple.com

The Apple logo is a trademark of Apple Inc., registered in the U.S. and other countries. Use of the "keyboard" Apple logo (Option-Shift-K) for commercial purposes without the prior written consent of Apple may constitute trademark infringement and unfair competition in violation of federal and state laws.

Apple, the Apple logo, AppleShare, AppleTalk, Mac, Macintosh, QuickTime, Xgrid, and Xserve are trademarks of Apple Inc., registered in the U.S. and other countries. Finder is a trademark of Apple Inc.

Adobe and PostScript are trademarks of Adobe Systems Incorporated.

Intel, Intel Core, Xeon are trademarks of Intel Corp. in the U.S. and other countries.

PowerPC™ and the PowerPC logo™ are trademarks of International Business Machines Corporation, used under license therefrom.

UNIX is a registered trademark of The Open Group.

Other company and product names mentioned herein are trademarks of their respective companies. Mention of third-party products is for informational purposes only and constitutes neither an endorsement nor a recommendation. Apple assumes no responsibility with regard to the performance or use of these products.

019-1423/2009-05-29

Contents

9	Preface: About This Guide
9	What's New in System Imaging and Software Update
9	What's in This Guide
10	Using Onscreen Help
11	Documentation Map
11	Viewing PDF Guides Onscreen
12	Printing PDF Guides
12	Getting Documentation Updates
13	Getting Additional Information

Part I: System Imaging Administration

16	Chapter 1: Understanding System Imaging
17	Inside NetBoot Service
17	Disk Images
19	NetBoot Image Folder
20	Property List File
21	Boot Server Discovery Protocol (BSDP)
21	BootP Server
22	Boot Files
22	Trivial File Transfer Protocol (TFTP)
22	Using Images Stored on Other Servers
22	Security
23	NetInstall Images
23	Tools for Managing NetBoot Service
24	Server Admin
24	Workgroup Manager
24	System Image Utility
25	Command-Line Tools
26	Chapter 2: Creating NetBoot and NetInstall Images
26	Using System Image Utility
26	Creating Images

27	Creating NetBoot Images
28	Creating NetInstall Images
29	Creating NetRestore Images
30	Creating an Image from a Configured Computer
32	Updating an Image
33	Understanding Workflows
33	Workflow Components
33	Configuring the Customize Package Selection Action
34	Configuring the Define Image Source Action
34	Configuring the Add Packages and Post-Install Scripts Action
35	Configuring the Add User Account Action
35	Configuring the Apply System Configuration Settings Action
36	Configuring the Create Image Action
36	Configuring the Enable Automated Installation Action
37	Configuring the Filter Clients by MAC Address Action
37	Configuring the Filter Computer Models Action
38	Configuring the Partition Disk Action
38	Assembling Workflows
39	Adding Existing Workflows
39	Removing Workflows
39	Assembling an Image Workflow
41	Adding Software to NetBoot and NetInstall Images
41	About Packages
41	Creating Packages
42	Viewing the Contents of a Package
43	Chapter 3: Setting Up NetBoot Service
43	Setup Overview
44	Before Setting Up NetBoot Service
45	What You Must Know
45	Client Computer Requirements
45	Network Hardware Requirements
46	Network Service Requirements
46	Capacity Planning
47	Serial Number Considerations
47	Turning NetBoot Service On
48	Setting Up NetBoot Service
48	Configuring NetBoot General Settings
48	Configuring Images Settings
49	Configuring Filters Settings
50	Configuring NetBoot Logging Settings
50	Enabling NetBoot 1.0 for Older NetBoot Clients
51	Starting NetBoot and Related Services

52	Managing Images
52	Enabling Images
52	Choosing Where Images Are Stored
54	Choosing Where Shadow Files Are Stored
55	Using Images Stored on Remote Servers
56	Specifying the Default Image
57	Setting an Image for Diskless Booting
58	Restricting NetBoot Clients by Filtering Addresses
59	Setting Up NetBoot Service Across Subnets
60	Chapter 4: Setting Up Clients to Use NetBoot and NetInstall Images
60	Setting Up Diskless Clients
60	Selecting a NetBoot Boot Image
61	Imaging Multiple Clients Using the Multicast asr Command
62	Selecting a NetInstall Image
62	Starting Up Using the N Key
63	Changing How NetBoot Clients Allocate Shadow Files
64	Chapter 5: Managing NetBoot Service
64	Controlling and Monitoring NetBoot
64	Turning Off NetBoot Service
65	Disabling a Boot or Installation Image
65	Viewing a List of NetBoot Clients
66	Viewing a List of NetBoot Connections
66	Checking the Status of NetBoot and Related Services
67	Viewing the NetBoot Service Log
67	Performance and Load Balancing
67	Load Balancing NetBoot Images
68	Distributing NetBoot Images Across Servers
68	Distributing NetBoot Images Across Server Disk Drives
69	Balancing NetBoot Image Access
70	Distributing Shadow Files
71	Chapter 6: Solving System Imaging Problems
71	General Tips
71	If NetBoot Client Computers Won't Start
72	If You Want to Change the Image Name
72	Changing the Name of an Uncompressed Image
72	Changing the Name of a Compressed Image

Part II: Software Update Administration

76 Chapter 7: Understanding Software Update Administration

- 76 Inside the Software Update Process
 - 77 Overview
 - 77 Catalogs
 - 77 Installation Packages
 - 78 Staying Up-To-Date with the Apple Server
 - 78 Limiting User Bandwidth
 - 78 Revoked Files
 - 78 Software Update Package Format
 - 79 Log Files
- 79 Information That Is Collected
- 79 Tools for Managing Software Update
 - 79 Server Admin
 - 80 Workgroup Manager
 - 80 Command-Line Tools

81 Chapter 8: Setting Up Software Update

- 81 Setup Overview
- 82 Considerations and Requirements
 - 82 What You Must Know
 - 82 Client Computer Requirements
 - 82 Network Hardware Requirements
 - 83 Capacity Planning
- 83 Before Setting Up Software Update
 - 83 Consider Which Software Update Packages to Offer
 - 84 Software Update Storage
 - 84 Organize Your Enterprise Client Computers
- 85 Turning Software Update On
- 85 Setting Up Software Update
- 85 Configuring Software Update General Settings
 - 86 Configuring Updates Settings
 - 87 Starting Software Update
- 87 Pointing Unmanaged Clients to a Software Update Server

89 Chapter 9: Managing Software Update

- 89 Manually Refreshing the Updates Catalog from the Apple Server
- 89 Checking the Status of Software Update
- 90 Stopping Software Update
- 90 Limiting User Bandwidth for Software Update
- 90 Automatically Copying and Enabling Updates from Apple
- 91 Copying and Enabling Selected Updates from Apple

- 92 Removing Updates from a Software Update Server
- 93 Identifying Individual Software Update Files

- 94 **Chapter 10: Solving Software Update Problems**
- 94 General Tips
- 94 If a Client Computer Can't Access the Software Update Server
- 94 If the Software Update Server Won't Sync with the Apple Server
- 94 If Update Packages That the Software Update Server Lists Aren't Visible to Client Computers

- 95 **Appendix: Command-Line Parameters**
- 95 NetBoot Service Settings
 - 95 The Storage Record Array
 - 96 The Filters Record Array
 - 96 The Image Record Array
 - 97 The Port Record Array

- 99 **Index**

About This Guide

This guide describes how to configure and use NetBoot and NetInstall images within Mac OS X Server. It also describes Software Update service, which you can set up using Mac OS X Server.

Mac OS X Server version 10.6 includes NetBoot service supporting NetBoot and NetInstall images and the improved System Image Utility—a stand-alone utility used to create Install and Boot images used with NetBoot service.

Mac OS X Server v10.6 also includes Apple's Software Update service. It is designed as a source for Apple Software Updates managed on your network. With Software Update, you can directly manage which Apple software updates users on your network can access and apply to their computers.

What's New in System Imaging and Software Update

NetBoot service, System Image Utility, and Software Update offer major enhancements in several key areas:

- **NetRestore Image:** System Image Utility allows you to create a NetRestore image that you can use to restore a volume over the network.
- **Software Update storage:** The Software Update catalog and downloads can be stored on another volume to free up space on the boot volume.

What's in This Guide

This guide includes the following sections:

- **Part I: System Imaging Administration.** The chapters in this part of the guide introduce you to system imaging and the applications and tools available for administering System Image Utility.
- **Part II: Software Update Administration.** The chapters in this part of the guide introduce you to Software Update and the applications and tools available for administering it.

Note: Because Apple periodically releases new versions and updates to its software, images shown in this book may be different from what you see on your screen.

Using Onscreen Help

You can get task instructions onscreen in Help Viewer while you're managing Mac OS X Server. You can view help on a server or on an administrator computer. (An administrator computer is a Mac OS X computer with Mac OS X Server administrator software installed on it.)

To get the most recent onscreen help for Mac OS X Server:

- Open Server Admin or Workgroup Manager and then:
 - Use the Help menu to search for a task you want to perform.
 - Choose Help > Server Admin Help or Help > Workgroup Manager Help to browse and search the help topics.

The onscreen help contains instructions taken from *Advanced Server Administration* and other administration guides.


To see the most recent server help topics:

- Make sure the server or administrator computer is connected to the Internet while you're getting help.

Help Viewer automatically retrieves and caches the most recent server help topics from the Internet. When not connected to the Internet, Help Viewer displays cached help topics.

Documentation Map

Mac OS X Server has a suite of guides that cover management of individual services. Each service may depend on other services for maximum utility. The documentation map below shows some related guides that you may need in order to fully configure System Imaging and Software Update to your specifications. You can get these guides in PDF format from the Mac OS X Server Resources website at www.apple.com/server/macosx/resources/.



Viewing PDF Guides Onscreen

While reading the PDF version of a guide onscreen:

- Show bookmarks to see the guide's outline, and click a bookmark to jump to the corresponding section.

- Search for a word or phrase to see a list of places where it appears in the document. Click a listed place to see the page where it occurs.
- Click a cross-reference to jump to the referenced section. Click a web link to visit the website in your browser.

Printing PDF Guides

If you want to print a guide, you can take these steps to save paper and ink:

- Save ink or toner by not printing the cover page.
- Save color ink on a color printer by looking in the panes of the Print dialog for an option to print in grays or black and white.
- Reduce the bulk of the printed document and save paper by printing more than one page per sheet of paper. In the Print dialog, change Scale to 115% (155% for *Getting Started*). Then choose Layout from the untitled pop-up menu. If your printer supports two-sided (duplex) printing, select one of the Two-Sided options. Otherwise, choose 2 from the Pages per Sheet pop-up menu, and optionally choose Single Hairline from the Border menu. (If you're using Mac OS X v10.4 or earlier, the Scale setting is in the Page Setup dialog and the Layout settings are in the Print dialog.)

You may want to enlarge the printed pages even if you don't print double sided, because the PDF page size is smaller than standard printer paper. In the Print dialog or Page Setup dialog, try changing Scale to 115% (155% for *Getting Started*, which has CD-size pages).

Getting Documentation Updates

Periodically, Apple posts revised help pages and new editions of guides. Some revised help pages update the latest editions of the guides.

- To view new onscreen help topics for a server application, make sure your server or administrator computer is connected to the Internet and click "Latest help topics" or "Staying current" in the main help page for the application.
- To download the latest guides in PDF format, go to the Mac OS X Server Resources website at www.apple.com/server/resources/.
- An RSS feed listing the latest updates to Mac OS X Server documentation and onscreen help is available. To view the feed use an RSS reader application such as Safari or Mail and go to:
`feed://helposx.apple.com/rss/snowleopard/serverdocupdates.xml`

Getting Additional Information

For more information, consult these resources:

- *Read Me documents*—get important updates and special information. Look for them on the server discs.
- *Mac OS X Server website* (www.apple.com/server/macosx/)—enter the gateway to extensive product and technology information.
- *Mac OS X Server Support website* (www.apple.com/support/macosxserver/)—access hundreds of articles from Apple’s support organization.
- *Apple Discussions website* (discussions.apple.com/)—share questions, knowledge, and advice with other administrators.
- *Apple Mailing Lists website* (www.lists.apple.com/)—subscribe to mailing lists so you can communicate with other administrators using email.
- *Apple Training and Certification website* (www.apple.com/training/)—hone your server administration skills with instructor-led or self-paced training, and differentiate yourself with certification.
- *Open Source website* (developer.apple.com/darwin/)—Access to Darwin open source code, developer information, and FAQs.

Part I: System Imaging Administration

The chapters in this part of the guide introduce you to system imaging and the applications and tools available for administering System Image Utility.

Chapter 1	Understanding System Imaging
Chapter 2	Creating NetBoot and NetInstall Images
Chapter 3	Setting Up NetBoot Service
Chapter 4	Setting Up Clients to Use NetBoot and NetInstall Images
Chapter 5	Managing NetBoot Service
Chapter 6	Solving System Imaging Problems

Understanding System Imaging

1

Use this chapter to learn the basics of how to start client computers using an operating system stored on a server and how to install software on client computers over the network.

The NetBoot, NetInstall, and NetRestore features of Mac OS X Server offer you alternatives for managing the operating system and application software that your Macintosh clients (or even other servers) require to start and do their work.

Instead of going from computer to computer to install operating system and application software from CDs, you can prepare an installation image that installs on each computer when it starts up.

You can also choose to not install software and have client computers start (or boot) from an image stored on the server. (In some cases, clients don't even need their own hard disk.)

Using NetBoot and NetInstall, your client computers can start from a standardized Mac OS configuration suited to specific tasks. Because the client computers start from the same image, you can quickly update the operating system for users by updating a single boot image.

A *boot image* is a file that looks and acts like a mountable disk or volume. NetBoot images contain the system software needed to act as a startup disk for client computers over the network.

An *installation image* is an image that starts up the client computer long enough to install software from the image. The client can then start up from its own hard disk.

Boot images (used with NetBoot) and installation images (used with NetInstall) are different kinds of disk images. The main difference is that a .dmg file is a proper disk image and a .nbi folder is a bootable network volume (which contains a .dmg disk image file). Disk images are files that behave like disk volumes.

You can set up multiple NetBoot or NetInstall images to suit the needs of different groups of clients or you can provide copies of the same image on multiple NetBoot servers to distribute the client startup load. You can also use a NetRestore image to quickly restore a volume.

NetBoot service can be used with NetBoot and NetInstall images along with Mac OS X client management services to provide a personalized work environment for each user. For information about client management services, see *User Management*.

You can use the following Mac OS X Server applications to set up and manage NetBoot, NetInstall, and NetRestore:

- *System Image Utility* to create Mac OS X NetBoot, NetInstall, and NetRestore disk images. This utility is installed with Mac OS X Server software in the `/Applications/Server/` folder.
- *Server Admin* to enable and configure NetBoot service and supporting services. This utility is installed with Mac OS X Server software in the `/Applications/Server/` folder.
- *PackageMaker* to create package files that you use to add software to disk images. This utility is provided on the *Mac OS X Server Administration Tools* CD.
- *Property List Editor* to edit property lists such as `NBIImageInfo.plist`. This utility is included on the *Mac OS X Server Administration Tools* CD.

Note: To create an image, you must have valid Mac OS X v10.6 image sources (either volumes or install DVDs). You cannot create an image of the startup disk you are running on.

Inside NetBoot Service

This section describes how NetBoot service is implemented on Mac OS X Server, including information about the protocols, files, folder structures, and configuration details.

Disk Images

The disk images contain the system software and applications used over the network by client computers. These tools can be installed on a client computer with the *Mac OS X Server Administration Tools* CD. The name of a disk image file typically ends in `.img` or `.dmg`. Disk Utility—part of Mac OS X—can mount disk image files as volumes on the desktop.

You use System Image Utility to create Mac OS X NetBoot or NetInstall images, using a Mac OS X installation disc or an existing system volume as the source. See “Creating Images” on page 26.

NetBoot Share Points

NetBoot service sets up share points to make images and shadow files available to clients. Shadow files are used for NetBoot clients that don't use their local hard disks to write out data when booted.

NetBoot service creates share points for storing NetBoot and NetInstall images in `/Library/NetBoot/` on each volume you enable and names them `NetBootSP n` , where n is 0 for the first share point and increases by 1 for each extra share point.

For example, if you decide to store images on three server disks, NetBoot service sets up three share points named `NetBootSP0`, `NetBootSP1`, and `NetBootSP2`.

The share points for client shadow files are also created in `/Library/NetBoot/` and are named `NetBootClients n` , where n is the share point number.

You can create and enable `NetBootSP n` and `NetBootClients n` share points on other server volumes using the NetBoot Service General settings in Server Admin.

WARNING: Don't rename a NetBoot share point or the volume it resides on. Don't stop sharing a NetBoot share point unless you first deselect the share point for images and shadow files in Server Admin.

Using NetBoot and NetInstall Images on Other Servers

You can also specify the path of a NetBoot image residing on a different NFS server. When creating image files, you can specify which server the image will reside on. See "Using Images Stored on Remote Servers" on page 55.

Client Information File

NetBoot service gathers information about a client the first time a client selects a NetBoot or NetInstall volume to start from the Startup Disk. NetBoot service stores this information in the `/var/db/bsdpd_clients` file.

Shadow Files

Many clients can read from the same NetBoot image, but when a client must write back to its startup volume (such as print jobs and other temporary files), NetBoot service redirects the written data to the client's *shadow* files, which are separate from regular system and application software.

Shadow files preserve the unique identity of each client while it is running from a NetBoot image. NetBoot service transparently maintains changed user data in shadow files while reading unchanged data from the shared system image. Shadow files are recreated at startup, so changes made to a user's startup volume are lost at restart.

For example, if a user saves a document to the startup volume, after a restart that document is gone. This behavior preserves the condition of the environment the administrator set up. Therefore users must have accounts on a file server on the network to save documents.

Balancing the Shadow File Load

NetBoot service creates an AFP share point on each server volume you specify (see “Choosing Where Shadow Files Are Stored” on page 54) and distributes client shadow files across them as a way of balancing the load for NetBoot clients. There is no performance gain if the volumes are partitions on the same disk. See “Distributing Shadow Files” on page 70.

Allocation of Shadow Files for Mac OS X NetBoot Clients

When a client computer starts from a Mac OS X NetBoot image, it creates shadow files on a server NetBootClients n share point or, if no share point is available, on a drive local to the client. For information about changing this behavior, see “Choosing Where Shadow Files Are Stored” on page 54.

NetBoot Image Folder

When you create a Mac OS X NetBoot image with System Image Utility, the utility creates a NetBoot image folder whose name ends with .nbi and stores in it the NetBoot image with other files (see the following table) required to start a client computer over the network.

File	Description
booter	Startup file that the firmware uses to begin the startup process
mach.macosx	UNIX kernel
mach.macosx.mkext	Drivers
System.dmg	Startup image file (can include application software)
NBImageInfo.plist	Property list file

System Image Utility stores the folder whose name ends with .nbi on the NetBoot server in `/Library/NetBoot/NetBootSP n /image.nbi` (where n is the volume number and *image* is the name of the image). You can save directly to this folder or you can create the image elsewhere (even on another computer) and copy it to the `/Library/NetBoot/NetBootSP n` folder later.

Files for PowerPC-based Macintosh computers are stored in the ppc folder for Mac OS X Server v10.5 images, while previous images might store PowerPC files in the root of the .nbi folder. Files for Intel-based Macintosh computers are stored in the i386 folder. Mac OS X Server v10.6 and later do not support imaging of PowerPC-based computers.

You use System Image Utility to set up NetBoot image folders. The utility lets you:

- Name the image
- Choose the image type (NetBoot or NetInstall)
- Provide an image ID
- Choose the default language
- Choose the computer models the image supports
- Create unique sharing names
- Specify a default user name and password
- Enable automatic installation for installation images
- Add package or preinstalled applications

For more information, see “Creating NetBoot Images” on page 27.

Property List File

The property list file NBIImageInfo.plist stores image properties. The following table gives more information about the property list file for Mac OS X image files.

Property	Type	Description
Architectures	Array	An array of strings of the architectures the image supports.
BootFile	String	Name of boot file: booter.
Index	Integer	1–4095 indicates a local image unique to the server. 4096–65535 is a duplicate, identical image stored on multiple servers for load balancing.

Property	Type	Description
IsDefault	Boolean	<i>True</i> specifies this image file as the default boot image on the subnet.
IsEnabled	Boolean	Sets whether the image is available to NetBoot (or Network Image) clients.
IsInstall	Boolean	<i>True</i> specifies a Network Install image; <i>False</i> specifies a NetBoot image.
Name	String	Name of the image as it appears in the Mac OS X Preferences pane.
RootPath	String	Specifies the path to the disk image on the server, or the path to an image on another server. See “Using Images Stored on Other Servers” on page 22.
Type	String	NFS or HTTP.
SupportsDiskless	Boolean	<i>True</i> directs the NetBoot server to allocate space for the shadow files needed by diskless clients.
Description	String	Text describing the image.
Language	String	A code specifying the language to be used while starting from the image.

Initial values in `NBImageInfo.plist` are set by System Image Utility and you usually don't need to change the property list file directly. Some values are set by Server Admin. If you must edit a property list file, you can use TextEdit or Property List Editor, found in the Utilities folder on the *Mac OS X Server Administration Tools* CD.

Boot Server Discovery Protocol (BDSP)

NetBoot service uses an Apple-developed protocol based on DHCP known as Boot Server Discovery Protocol (BDSP). This protocol provides a way of discovering NetBoot servers on a network.

NetBoot clients obtain their IP information from a DHCP server and their NetBoot information from BDSP. BDSP offers built-in support for load balancing. See “Performance and Load Balancing” on page 67.

BootP Server

NetBoot service uses a BootP server (bootpd) to provide necessary information to client computers when they try to start from an image on the server.

If BootP clients on your network request an IP address from the NetBoot BootP server, this request fails because the NetBoot BootP server doesn't have addresses to offer. To prevent the NetBoot BootP server from responding to requests for IP addresses, use the `dscl` command-line tool to open the local folder on the NetBoot server and add a key named `bootp_enabled` with no value to the `/config/dhcp/` folder.

Boot Files

When you create a Mac OS X NetBoot image with System Image Utility, the utility generates the following boot files and stores them on the NetBoot server in `/Library/NetBoot/NetBootSPn/image.nbi` (where *n* is the volume number and *image* is the name of the image):

- `booter`
- `mach.macosx`
- `mach.macosx.mkext`

Note: If you turn on NetBoot service when installing Mac OS X Server, the installer creates the NetBootSP0 share point on the server boot volume. Otherwise, you can set up NetBootSP*n* share points by choosing where to store NetBoot images from the list of volumes in the General pane of NetBoot Service settings in Server Admin.

Trivial File Transfer Protocol (TFTP)

NetBoot service uses Trivial File Transfer Protocol (TFTP) to send boot files from the server to the client. When you start a NetBoot client, the client sends a request for startup software. The NetBoot server then delivers the booter file to the client using TFTP default port 69.

Client computers access the startup software on the NetBoot server from the location where the image was saved.

These files are typically stored in the `/private/tftpboot/NetBoot/NetBootSPn/` folder. This path is a symbolic link to `Library/NetBoot/NetBootSPn/image.nbi` (where *n* is the volume number and *image* is the name of the image).

Using Images Stored on Other Servers

You can store Mac OS X NetBoot or NetInstall images on NFS servers other than the NetBoot server. For more information, see "Using Images Stored on Remote Servers" on page 55.

Security

You can restrict access to NetBoot service on a case-by-case basis by listing the hardware addresses (also known as the Ethernet or MAC addresses) of computers that you want to permit or deny access to.

The hardware address of a client computer is added to the NetBoot Filtering list when the client starts up using NetBoot and is, by default, enabled to use NetBoot service. You can specify other services. See “Restricting NetBoot Clients by Filtering Addresses” on page 58.

NetInstall Images

A NetInstall image is an image that starts up the client computer long enough to install software from the image. The client can then start up from its own hard disk. In the same way that a NetBoot image replaces the role of a hard disk, a NetInstall image is a replacement for an installation DVD.

Like a bootable CD, NetInstall is a convenient way to reinstall the operating system, applications, or other software onto the local hard disk. For system administrators deploying large numbers of computers with the same version of Mac OS X, NetInstall can be very useful. NetInstall does not require the insertion of a CD into each NetBoot client because startup and installation information is delivered over the network.

When you create a NetInstall image with System Image Utility, you can automate the installation process by limiting interaction at the client computer.

Because an automatic network installation can be configured to erase the contents of the local hard disk before installation, data loss can occur. You must control access to this type of NetInstall image and must communicate the implications of using them to those using these images. Before using automatic network installations, it is always wise to inform users to back up critical data.

You can perform software installations through NetInstall using a collection of packages or an entire disk image (depending on the source used to create the image).

For more information about preparing NetInstall images to install software over the network, see “Creating NetInstall Images” on page 28.

Tools for Managing NetBoot Service

The Server Admin and System Image Utility applications provide a graphical interface for managing NetBoot service in Mac OS X Server. In addition, you can manage NetBoot service from the command line by using Terminal.

These applications are included with Mac OS X Server and can be installed on another computer with Mac OS X v10.6 or later, making that computer an administrator computer. For more information about setting up an administrator computer, see the server administration chapter of *Getting Started*.

Server Admin

Server Admin provides access to tools you use to set up, manage, and monitor NetBoot service and other services. You use Server Admin to:

- Set up Mac OS X Server as a DHCP server and configure NetBoot service to use NetBoot and NetInstall images. For instructions, see Chapter 3, “Setting Up NetBoot Service.”
- Manage and monitor NetBoot service. For instructions, see Chapter 5, “Managing NetBoot Service.”

For more information about using Server Admin, see *Advanced Server Administration*. This guide includes information about:

- Opening and authenticating in Server Admin
- Working with specific servers
- Administering services
- Using SSL for remote server administration
- Customizing the Server Admin environment

Server Admin is installed in `/Applications/Server/`.

Workgroup Manager

The Workgroup Manager application provides comprehensive management of clients of Mac OS X Server. For basic information about using Workgroup Manager, see *User Management*. This includes:

- Opening and authenticating in Workgroup Manager
- Administering accounts
- Customizing the Workgroup Manager environment

Workgroup Manager is installed in `/Applications/Server/`.

System Image Utility

System Image Utility is a tool you use to create and customize NetBoot, NetInstall, and NetRestore images. With System Image Utility, you can:

- Create NetBoot images that can be booted to the Finder.
- Create NetInstall images from a DVD or existing Mac OS X partition.
- Create NetRestore images from an existing volume.
- Assemble a workflow that creates customized NetBoot and NetInstall images.

For instructions on using System Image Utility, see Chapter 2, “Creating NetBoot and NetInstall Images.”

System Image Utility is installed in `/Applications/Server/`.

Command-Line Tools

A full range of command-line tools is available for administrators who prefer to use command-driven server administration. For remote server management, submit commands in a secure shell (SSH) session. You can enter commands on Mac OS X servers and computers using the Terminal application, located in the /Applications/Utilities/ folder.

Creating NetBoot and NetInstall Images

2

Use this chapter to prepare NetBoot, NetInstall, and NetRestore images used with NetBoot service or Apple Software Restore.

You can set up multiple NetBoot or NetInstall images to suit the needs of different groups of users or to provide copies of the same image on multiple servers to distribute the client startup load. You can also set up NetRestore images to restore Mac OS X volumes. Using NetBoot service, you can provide a personalized work environment for each user.

Using System Image Utility

System Image Utility is a tool you use to create and customize NetBoot, NetInstall, and NetRestore images.

With System Image Utility, you can:

- Create NetBoot images that can be booted using Finder.
- Create NetInstall images from a DVD or existing Mac OS X partition.
- Create NetRestore images from an existing Mac OS X volume.
- Assemble a workflow that creates customized NetBoot and NetInstall images.

Creating Images

To create system and software images to use with NetBoot service or the `asr` tool, use System Image Utility.

Note: To create an image, you must have valid Mac OS X v10.6 image sources (volumes or installation DVDs). You cannot create an image of the startup disk you are running on.

Creating NetBoot Images

You can create NetBoot images of Mac OS X that are then used to start client computers over the network.

You can also assemble a workflow to create a NetBoot image that permits advanced customization of your images. For more information, see “Understanding Workflows” on page 33.

Note: You must purchase a Mac OS X user license for each client that starts from a NetBoot or NetInstall disk image.

To create a NetBoot image:

- 1 Log in as an administrator user.
- 2 Open System Image Utility (in the /Applications/Server/ folder).
- 3 In the left sidebar, select the image source.

If no image sources are listed, make sure you inserted a valid Mac OS X v10.6 or later installation DVD or mounted a valid Mac OS X v10.6 or later boot volume.

Note: To create an image, you must have valid Mac OS X v10.6 image sources (volumes or installation DVDs). You cannot create an image of the startup disk you are running on.

- 4 Select NetBoot Image and click Continue.
- 5 In the Network Disk field, enter a name for your image.
This name identifies the image in the Startup Disk preferences pane on client computers.
- 6 (Optional) In the Description field, enter notes or other information to help you characterize the image.
Clients can't see the description information.
- 7 If the image will be served from more than one server, select the checkbox below the description field.
This option generates an index ID for NetBoot server load balancing.
- 8 If your source volume is a Mac OS X Installation DVD, enter a user name, short name, and password (in the Password and Verify fields) for the administrator account in Create Administrator Account.
You can log in to a booted client using this account.
- 9 Click Create.
- 10 In the Save As dialog, choose where to save the image.

If you don't want to use the image name you entered earlier, change it by entering a new name in the Save As field.

NetBoot service must be configured on a network port and Server Admin must be set to serve images from a volume for this option to appear in the pop-up menu. For more information, see “Setting Up NetBoot Service” on page 48.

To save the image somewhere else, choose a location from the Where pop-up menu or click the triangle next to the Save As field and navigate to a folder.

- 11 Click Save and authenticate if prompted.

Important: Do not attempt to edit content in the image destination folder while the image is being created.

Creating NetInstall Images

Use System Image Utility to create a NetInstall image that you can use to install software on client computers over the network. You can find this application in the /Applications/Server/ folder.

To create a NetInstall image:

- 1 Log in as an administrator user.
- 2 Open System Image Utility (in the /Applications/Server/ folder).
- 3 In the left sidebar select the image source.

If no image sources are listed, make sure you inserted a valid Mac OS X v10.6 or later installation DVD or mounted a valid Mac OS X v10.6 or later boot volume.

Note: To create an image, you must have valid Mac OS X v10.6 image sources (volumes or installation DVDs). You cannot create an image of the startup disk you are running on.

- 4 Select NetInstall Image and click Continue.
- 5 In the Network Disk field, enter a name for your image.
This name identifies the image in the Startup Disk preferences pane on client computers.
- 6 (Optional) In the Description field, enter notes or other information to help you characterize the image.
Clients can't see the description information.
- 7 If the image will be served from more than one server, select the checkbox below the description field.
This assigns an index ID to the image for NetBoot service load balancing.
- 8 Click Create.
- 9 In the Save As dialog, choose where to save the image.

If you don't want to use the image name you entered earlier, change it by entering a new name in the Save As field.

If you're creating the image on the same server that will serve it, choose a volume from the Serve from NetBoot share point on pop-up menu.

NetBoot service must be configured on a network port and Server Admin must be set to serve images from a volume for this option to appear in the pop-up menu. For more information, see "Setting Up NetBoot Service" on page 48.

To save the image somewhere else, choose a location from the Where pop-up menu or click the triangle next to the Save As field and navigate to a folder.

- 10 Click Save and authenticate if prompted.

Important: Do not attempt to edit content in the image destination folder while the image is being created.

Creating NetRestore Images

If you have a client computer that's already configured, you can use System Image Utility to create a NetRestore image based on that client configuration. You can create a NetRestore image of a Mac OS X volume that is used to restore client computers over the network using NetBoot service or Apple Software Recovery `asr`. When you create a NetRestore image you are creating a clone of a volume.

You can also use the `asr` tool to restore a system image onto a volume or to clone volumes.

You must start up from a volume other than the one you're using as the image source. For example, you could start up from an external FireWire hard disk or a second partition on the client computer hard disk. You can't create the image on a volume over the network.

You can also assemble a workflow to create a NetRestore image that permits advanced customization of your images. For more information, see "Understanding Workflows" on page 33.

To create a NetRestore image:

- 1 Log in as an administrator user.
- 2 Open System Image Utility (in the /Applications/Server/ folder).
- 3 In the left sidebar, select the image source.

If no image sources are listed, make sure you inserted a valid Mac OS X v10.6 or later installation DVD or mounted a valid Mac OS X v10.6 or later boot volume.

Note: To create an image, you must have valid Mac OS X v10.6 image sources (volumes or installation DVDs). You cannot create an image of the startup disk you are running on.

- 4 Select NetRestore Image and click Continue.
- 5 In the Network Disk field, enter a name for your image.

This name identifies the image in the Startup Disk preferences pane on client computers.

- 6 (Optional) In the Description field, enter notes or other information to help you characterize the image.

Clients can't see the description information.

- 7 If the image will be served from more than one server, select the checkbox below the description field.

This assigns an index ID to the image for NetBoot service load balancing.

- 8 Click Create.

- 9 In the Save As dialog, choose where to save the image.

If you don't want to use the image name you entered earlier, change it by entering a new name in the Save As field.

If you're creating the image on the same server that will serve it, choose a volume from the Serve from NetBoot share point on pop-up menu.

NetBoot service must be configured on a network port and Server Admin must be set to serve images from a volume for this option to appear in the pop-up menu. For more information, see "Setting Up NetBoot Service" on page 48.

To save the image somewhere else, choose a location from the Where pop-up menu or click the triangle next to the Save As field and navigate to a folder.

- 10 Click Save and authenticate if prompted.

Important: Do not attempt to edit content in the image destination folder while the image is being created.

From the Command Line:

When using `asr` to restore a volume, the target disk is erased.

- To clone a volume:

```
$ sudo asr -source /Volumes/Classic -target /Volumes/install
```

- To restore a system image onto a volume:

```
$ sudo asr -source compressedimage -target <targetvol> -erase
```

Creating an Image from a Configured Computer

If a client computer is already configured, you can use System Image Utility to create a NetBoot or NetInstall image based on that client configuration.

You must start up from a volume other than the one you're using as the image source. For example, you could start up from an external FireWire hard disk or a second partition on the client computer hard disk. You can't create the image on a volume over the network.

To create an image based on an existing system:

- 1 Start up the computer from a partition other than the one you're imaging.
- 2 Install System Image Utility on the client computer from the *Mac OS X Server Administration Tools* CD.
- 3 Open System Image Utility on the client computer (in the `/Applications/Server/` folder).

- 4 In the left sidebar, select the image source.

If no image sources are listed, make sure you inserted a valid Mac OS X v10.6 or later installation DVD or mounted a valid Mac OS X v10.6 or later boot volume.

Note: To create an image, you must have valid Mac OS X v10.6 image sources (volumes or installation DVDs). You cannot create an image of the startup disk you are running on.

- 5 From the expanded list, select the image source.
- 6 Select NetBoot Image, NetInstall Image, or NetRestore Image and click Continue.
 - Select NetBoot if your client computers will start up from this image.
 - Select NetInstall if your image will be installed on a hard disk.
 - Select NetRestore if your image is a clone of a volume.

- 7 In the Image Name field, enter a name for your image.

This name identifies the image in the Startup Disk preferences pane on client computers.

- 8 (Optional) In the Description field, enter notes or other information to help you characterize the image.

Clients can't see the description information.

- 9 If the image will be served from more than one server, select the checkbox below the description field.

This option generates an index ID for NetBoot server load balancing.

- 10 For NetBoot images, if your source volume is a Mac OS X Installation DVD, enter a user name, short name, and password (in the Password and Verify fields) for the administrator account in Create Administrator Account.

You can log in to a booted client using this account.

- 11 Click Create.

- 12 In the Save As dialog, choose where to save the image.

If you don't want to use the image name you entered earlier, change it by entering a new name in the Save As field.

To save the image somewhere else, choose a location from the Where pop-up menu or click the triangle next to the Save As field and navigate to a folder.

- 13 Click Save and authenticate if prompted.

Important: Do not attempt to edit content in the image destination folder while the image is being created.

- 14 After the image is created on the client computer, copy it to the `/Library/NetBoot/NetBootSPn` share point on the server for use by NetBoot service.

Images should be stored in this folder.

From the command line:

You can also create a NetBoot image clone of a system using the `hdiutil` command in Terminal to manipulate disk images. You can use this tool to perform many functions such as creating, compressing, mounting, unmounting, and resizing images. You can also display image information and burn images onto CDs.

- To verify an image by comparing it to its internal checksum:

```
$ hdiutil verify myimage.img
```

- To split an image into three segments:

```
$ hdiutil segment -segmentSize 10m -o /tmp/aseg 30m.dmg
```

This creates three files: `aseg.dmg`, `aseg.002.dmgpart`, and `aseg.003.dmgpart`.

- To convert an image to a CD, export image with a `.toast` extension:

```
$ hdiutil convert master.dmg -format UDTO -o master
```

- To burn an image onto a CD:

```
$ hdiutil burn myImage.dmg
```

- To create an image from a folder:

```
$ hdiutil create -srcfolder mydir mydir.dmg
```

For information about how to manipulate disk images, see the `hdiutil` man page.

For the basics of command-line tool usage, see *Introduction to Command-Line Administration*.

Updating an Image

To update a Mac OS X disk image, you must recreate the image. New images can easily be recreated by running a saved image creation workflow. For more information, see “Creating Images” on page 26.

From the command line:

To update a NetBoot image from the command line, use the `installer` tool the same way you would to install packages on your default installation volume.

- To update an image:

```
$ installer -pkg pkg.mpkg -target image_path
```

For information about `installer`, see its man page. For the basics of command-line tool usage, see *Introduction to Command-Line Administration*.

Understanding Workflows

System Image Utility now harnesses the power of Automator to help you create custom images by assembling workflows. The basic building block of a workflow is an automator action. You define the image customization by assembling automator actions into a workflow.

You use workflows to create customized NetInstall or NetBoot images depending on the goals of your task:

- Workflows that create custom NetInstall images assemble an image that installs the OS onto the computer, either originating from installation DVDs or from an installed OS volume. This image boots into the installer environment or similar shell environment and performs the workflow steps you define.
- Workflows that create custom NetBoot images assemble a bootable image from installation DVDs or from an installed OS volume. This is an image that could be directly installed onto a target volume using the `asr` command-line tool or you can use NetBoot.

Each action performs a single task, such as customizing a software package or adding a user account.

Instead of being a do-it-all tool, an action is purpose-designed to perform a single task well. By combining several actions into a workflow, you can quickly accomplish a specific task that no one action can accomplish on its own.

Workflow Components

System Image Utility comes preloaded with a library of actions. You can use these actions to customize settings when creating an image. You access and organize this Automator Library of actions within the workflow panes of System Image Utility.

The following sections describe the workflow actions available in the Automator Library and provide steps on how to configure their options. By themselves, these actions cannot create an image and must be assembled into a workflow to function. For more information, see “Assembling Workflows” on page 38.

Configuring the Customize Package Selection Action

Use this action to customize the installation of the Mac OS X. You can disable, enable, require, or prevent installation of packages or parts of packages in your image.

This action is only valid when creating NetInstall images.

To configure the Customize Package Selection workflow action:

- 1 From your System Image Utility workflow, select the Customize Package Selection action in the Automator Library and drag it into position in your workflow.

- 2 Enable or disable the installation of software packages using the Visible column:
 - Select the checkbox in the Visible column to enable the software package. If enabled, the user can install the package from your image during installation.
 - Deselect the checkbox in the Visible column to disable the software package. If disabled, the user cannot choose whether the package gets installed or not.
- 3 Require or prevent the installation of software packages using the Default and Visible columns:
 - To require the installation of the software package, select the checkbox in the Default column and deselect the checkbox in the Visible column. The user cannot alter the package installation.
 - To prevent the installation of the software package, deselect the checkbox in the Default column and deselect the checkbox in the Visible column. The user cannot see the package and the package will not be installed.

Configuring the Define Image Source Action

Use this action to select the source volume and the type of image to create from it. This action must be at the beginning of all image creation workflows.

This action is valid when creating NetBoot, NetInstall, and NetRestore images.

To configure the Define Image Source workflow action:

- 1 From your System Image Utility workflow, select the Define Image Source action in the Automator Library and drag it to the beginning of your workflow.
- 2 From the Source pop-up menu, select the image source.

Note: To create an image, you must have valid Mac OS X v10.6 image sources (volumes or installation DVDs). You cannot create an image of the startup disk you are running on.

Configuring the Add Packages and Post-Install Scripts Action

Use this action to add installer packages and post-install scripts to a NetInstall image. Post-install scripts provide the ability to customize each computer you deploy an image on.

This action is only valid when creating a NetInstall image.

To configure the Add Packages and Post-Install Scripts workflow action:

- 1 From your System Image Utility workflow, select the Add Packages and Post-Install Scripts action in the Automator Library and drag it into position in your workflow.
- 2 Add or Remove software packages or post-install scripts to your NetInstall image:
 - To add a package, click the Add (+) button, select the packages or post-install script you want to add to your NetInstall image, then click Open.

- To remove a package or post-install script, select the item from the list and click the Delete (-) button.

You can also drag items into the list from Finder and delete them by pressing the Delete key.

Configuring the Add User Account Action

Use this account to add a user account to the Mac OS X installation image. You can set this user to be an administrator.

Generally, a NetBoot computer created from a Mac OS X Installation DVD must have at least one administrator user account. You can log in to a booted client using this account.

This action is only valid when creating a NetBoot image.

To configure the Add User Account workflow action:

- 1 From your System Image Utility workflow, select the Add User Account action in the Automator Library and drag it into position in your workflow.
- 2 Enter a user name, short name, and password for the user account.
- 3 Select the “Allow user to administer the computer” checkbox to give the account administrator privileges.

Configuring the Apply System Configuration Settings Action

Use this action to set custom per-host settings on client computers.

This action is only valid when creating NetInstall images.

To configure the Apply System Configuration Settings workflow action:

- 1 From your System Image Utility workflow, select the Apply System Configuration Settings action in the Automator Library and drag it into position in your workflow.
- 2 Select from the following options to apply system configuration settings to your NetInstall image.
 - If you want to copy the directory services configuration from the computer you are creating the image from, select “Apply directory services settings from this machine to all clients.”
 - If you want to bind clients one by one to their respective server or servers, click the triangle next to “Map clients to other directory servers” and add or remove clients with the Add (+) and Delete (-) buttons below the list.

The Server column is the Open Directory server, Ethernet Address is the MAC address of the client computer, and User Name and Password are the administrator credentials for the Open Directory server.

- If you have a configuration file that contains the Computer Name and Local Hostname settings for your image, select “Apply Computer Name and Local Hostname settings from a file” and enter the path to the file (or click Select File and browse to the file).
- If you are creating an image for multiple computers, select “Generate unique Computer Names starting with” and enter the name in the field below. This gives each computer with a deployed image a unique name on your network.
- If you want the image to transfer the computer preferences of the computer you are creating the image from, select “Change ByHost preferences to match client after install.”

Configuring the Create Image Action

Use this action to produce a disk image that can be served from a NetBoot server. You must place this action at the end of all image creation workflows.

This action is valid when creating NetBoot, NetInstall, and NetRestore images.

To configure the Create Image workflow action:

- 1 From your System Image Utility workflow, select the Create Image action in the Automator Library and drag it to the end of your workflow.
- 2 From the Save To pop-up menu, choose where to save the image.
- 3 In the Image Named field, enter the name of the image file.
This name identifies the image file stored on the computer.
- 4 In the Network Disk field, enter a name for your image.
This name identifies the image in the Startup Disk preferences pane on client computers.
- 5 (Optional) In the Description field, enter notes or other information to help you characterize the image.
Clients can't see the description information.
- 6 In the Image Index field, enter an Image ID:
 - To create an image that is unique to this server, choose an ID in the range 1–4095.
 - To create one of several identical images to be stored on different servers for load balancing, use an ID in the range 4096–65535.
Multiple images of the same type with the same ID in this range are listed as a single image in a client's Startup Disk preferences pane.

Configuring the Enable Automated Installation Action

Use this action to set the options for automated (unattended) client installations.

This action is only valid when creating NetInstall or NetRestore images.

To configure the Enable Automated Installation workflow action:

- 1 From your System Image Utility workflow, select the Enable Automated Installation action in the Automator Library and drag it into position in your workflow.
- 2 Determine how you want the target volume to be selected.

This is the volume that the image will be installed on.

The Selected by user option permits users to select which volume on their client computer to install the image on.

The Named option permits you to set the volume without interaction from the user by entering the name of the target volume.

- 3 To erase the target volume before the image is installed, select the Erase before installing checkbox.

WARNING: Using the Erase option removes all data from the target volume. Back up all data before using this option.

- 4 From the Primary Language pop-up menu, choose the image language.

Configuring the Filter Clients by MAC Address Action

Use this action to restrict client access to NetBoot or NetInstall images.

This action is valid when creating NetBoot, NetInstall, or NetRestore images.

To configure the Filter Clients by MAC Address workflow action:

- 1 From your System Image Utility workflow, select the Filter Clients by MAC Address action in the Automator Library and drag it into position in your workflow.
- 2 Add MAC addresses to the list.

To manually enter MAC addresses, click the Add (+) button or click Import and browse to a .txt or .rtf file that has a tab-delimited list of MAC addresses.

To remove MAC addresses from the list, select the item to remove and click the Delete (-) button.

- 3 To restrict image access, choose Allow or Deny for each MAC address.

Configuring the Filter Computer Models Action

Use this action to limit the computer models that a Mac OS X image can be installed on. Only selected computer models have access to the image.

This action is only valid when creating NetInstall or NetRestore images.

To configure the Filter Computer Model workflow action:

- 1 From your System Image Utility workflow, select the Filter Computer Model action in the Automator Library and drag it into position in your workflow.

- 2 In the list, select the computer models you want to permit the image to install on. No other computer models will have access to the image.
Use the filter field in the upper right to narrow the list of computer models.

Configuring the Partition Disk Action

Use this action to configure the image to partition the destination disk before installing software. Partitioning a disk divides it into sections called volumes.

This action is only valid when creating NetInstall or NetRestore images.

To configure the Partition Disk workflow action:

- 1 From your System Image Utility workflow, select the Partition Disk action in the Automator Library and drag it into position in your workflow.
- 2 Define the number of partitions by choosing from the partition pop-up menu or by using the Split and Delete buttons to add or remove partitions.
- 3 Set the target disk to partition by selecting “Partition disk containing the volume” and entering the name of the volume.
This partitions the disk containing the volume you specify.
- 4 To notify the user before the disk is partitioned, select “Display confirmation dialog before erase.”

WARNING: Partitioning a disk removes all data. Back up all data before using this action.

- 5 In the Name field enter a name for the new volume (partition).
- 6 From the Format pop-up menu, select the volume format.
- 7 Set the size of the volume by choosing one of the following.
 - Choose “Percentage of available disk” from the Size pop-up menu and enter a percentage. Select Minimum and enter the smallest size in GB for the volume (minimum size is only available if using percentage).
 - Choose “Absolute size” from the Size pop-up menu and enter the size in GB.
- 8 To prevent the information from being updated when the disk is partitioned, select “Locked for editing.”

Assembling Workflows

To assemble a workflow from a set of actions, drag and drop the actions from the Automator Library into the sequence where you want them to run. Each action in the workflow corresponds to a step you must perform manually.

Each action has options and settings you can configure. System Image Utility connects these action components with the types of data that are flowing from one action to another.

You can save your assembled workflows to reuse later.

Adding Existing Workflows

You can update or modify workflows by adding them to System Image Utility.

To add existing workflows to System Image Utility:

- 1 Open System Image Utility.
- 2 Click the Add (+) button and select Add Existing Workflow.
- 3 Select the workflow you want to add to System Image Utility.

Workflows have the workflow file extension.

- 4 Click Open.

Removing Workflows

You can remove workflows from System Image Utility.

To remove a workflow from System Image Utility:

- 1 Log in as an administrator user and open System Image Utility.
- 2 In the left sidebar, click the triangle next to Workflows.

The list of workflows appears.

- 3 Select the workflow you want to remove and click File > Remove Workflow.
- 4 Click Remove to confirm the action.

The workflow is removed from System Image Utility but is not deleted from your computer.

Assembling an Image Workflow

Use image workflows to create Mac OS X NetBoot and NetInstall images. Workflows let you manually define the contents of your image in System Image Utility.

An image workflow must start with the Define Image Source action and end with the Create Image action. Also, all actions in a workflow must be connected. If not, the workflow is invalid and the actions are not processed.

To assemble an image workflow:

- 1 Log in as an administrator user.
- 2 Open System Image Utility (in the /Applications/Server/ folder).
- 3 In the image source list, click the triangle at the left of Sources.

The list of sources appears.

- 4 From the expanded list, select the image source.

When you select the source, this action chooses a default image type based on the contents of the selected source.

- 5 Choose which type of image you are creating (NetInstall, NetBoot, or NetRestore image).

- 6 Click Customize for advanced image creation options.

This opens the workflow pane and Automator Library.

The Define Image Source action is present as the first component in the workflow.

- 7 Configure the Define Image Source action for your image.

This action is required at the beginning of all image workflows. See “Configuring the Define Image Source Action” on page 34.

- 8 From Automator Library, choose additional actions that your customized image requires and drag them into the Workflow pane between the Define Image Source action and the Create Image action.

Assemble the actions in the order you like, configuring each action as you go.

For more information on configuring the actions, see “Workflow Components” on page 33.

- 9 Add the Create Image action to the end of your workflow.

This action is required at the end of image workflows. See “Configuring the Create Image Action” on page 36.

- 10 Save the workflow by clicking Save.

Enter the name of your workflow in the Save As field and choose where to save the workflow.

To save the workflow somewhere else, choose a location from the Where pop-up menu or click the triangle next to the Save As field and navigate to a folder.

- 11 Click Save.

- 12 To start the workflow, click Run and authenticate if prompted.

Important: Do not attempt to edit content in the image destination folder while the image is being created.

From the command line:

- To run a workflow with *somevariable* set to *somevalue* in the *myworkflow.workflow* file:

```
$ automator -D somevariable=somevalue myworkflow.workflow
```

To create or edit a workflow, use System Image Utility. For more information, see the `automator` man pages and the following sections:

- “Adding Existing Workflows” on page 39

- “Removing Workflows” on page 39
- “Workflow Components” on page 33

Adding Software to NetBoot and NetInstall Images

There are two basic approaches to including software in an image:

- Add applications and files to a system before creating an image using that system as the source. For more information, see “Creating an Image from a Configured Computer” on page 30.
- Add packages containing the applications and files to an image as it is created. This is done using an image workflow in System Image Utility that has the Customize Package Selection action component. For more information, see “Configuring the Customize Package Selection Action” on page 33.

About Packages

To add application software or other files at image creation (instead of installing applications or files on the image source volume before you create the image), you must group the applications or files in a special file known as a *package*.

A package is a collection of compressed files and related information used to install software onto a computer. The contents of a package are contained in a single file that has the .pkg extension.

Creating Packages

To add applications or other files to an image (instead of installing them on the image source volume before creating the image), use PackageMaker to create packages containing the application or files. PackageMaker is in the Utilities folder on the *Mac OS X Server Administration Tools* CD that comes with Mac OS X Server.

For more information about creating packages, open PackageMaker and choose PackageMaker Help, PackageMaker Release Notes, or Package Format Notes from the Help menu.

After creating packages, add them to your NetBoot or NetInstall image using System Image Utility workflows.

From the command line:

You can also run the `packagemaker` tool from the command line in Terminal on a computer with developer tools installed. You can access it from `/Developer/usr/bin/packagemaker`. For more information, open PackageMaker and choose PackageMaker Help, PackageMaker Release Notes, or Package Format Notes from the Help menu.

Viewing the Contents of a Package

To view the contents of a package, open a Finder window, hold down the Control key as you click the package, and choose Show Package Contents from the menu that appears.

You use PackageMaker (included on the *Mac OS X Server Administration Tools* CD) to create application software packages to use with NetInstall images.

From the command line:

- To list the contents of a package:

```
$ ls package
```

For information about `ls`, see its man page. For the basics of command-line tool usage, see *Introduction to Command-Line Administration*.

Setting Up NetBoot Service

3

Use this chapter to set up NetBoot service to make boot and installation images available to clients.

Use Server Admin to configure the NetBoot service in conjunction with System Image Utility to create and edit images.

Setup Overview

Here is an overview of the basic steps for setting up NetBoot service.

Step 1: Evaluate and update your network, servers, and client computers as necessary. The number of client computers you can support using NetBoot is determined by the number of servers you have, how they're configured, hard disk storage capacity, and other factors. See "Capacity Planning" on page 46.

Depending on the results of this evaluation, you might want to add servers or hard disks, add Ethernet ports to your server, or make other changes to your servers. You might also want to set up more subnets for BootP clients, depending on the number of clients you support.

You might also want to implement subnets on this server (or other servers) to take advantage of NetBoot filtering.

To provide authentication and personalized work environments for NetBoot client users by using Workgroup Manager, set up workgroups and import users from the Mac OS X Server Users & Groups database before you create disk images. Make sure you have at least one administrator user assigned to the Workgroup Manager for Mac OS X client.

Step 2: Create disk images for client computers. You can set up Mac OS X disk images for client computers to start from. To create Mac OS X disk images, you use System Image Utility. See "Creating Images" on page 26.

You might also want to restrict access to NetBoot images by using Model Filtering. See "Creating NetBoot Images" on page 27.

To create application packages that you can add to an image, use PackageMaker. Application software packages can be installed by themselves or with Mac OS X system software. See “Creating Packages” on page 41.

Step 3: Set up DHCP. NetBoot requires that you have a DHCP server running on the local server or on another server on the network. Make sure you have a range of IP addresses sufficient to accommodate the number of clients that will use NetBoot at the same time. For more information about configuring DHCP, see *Network Services Administration*.

If your NetBoot server also supplies DHCP service, you might get better performance if you configure your server as a gateway. That is, configure your subnets to use the server’s IP address as the router IP address.

Step 4: Configure and turn on NetBoot service. You use the NetBoot settings in Server Admin to configure NetBoot on your server. See “Setting Up NetBoot Service” on page 48.

You turn on NetBoot service using Server Admin. See “Starting NetBoot and Related Services” on page 51 and “Enabling Images” on page 52.

Step 5: (Optional) Set up Ethernet address filtering. NetBoot filtering is performed based on the client computer hardware address. Each client’s hardware address is registered when the client selects a NetBoot or NetInstall volume from the startup disk. You can permit or deny specific clients by address. See “Restricting NetBoot Clients by Filtering Addresses” on page 58.

Step 6: Test your NetBoot setup. Because there is a risk of data loss or bringing down the network (by misconfiguring DHCP), you should test your NetBoot setup before implementing it. Test each Macintosh model you support to verify that there are no problems booting into the image on a specified hardware type.

Step 7: Set up client computers to use NetBoot. When you’re satisfied that NetBoot is working on all types of client computers, set up the client computers to start from the NetBoot disk images.

You can use the client computer’s Startup Disk System Preference pane to select a startup disk image from the server and then restart the computer. See “Selecting a NetBoot Boot Image” on page 60.

You can also restart the client computer and hold down the N key until the NetBoot icon starts flashing on the screen. The client starts from the default image on the NetBoot server. See “Starting Up Using the N Key” on page 62.

Before Setting Up NetBoot Service

Before you set up NetBoot service, review the following considerations and requirements.

What You Must Know

Before you set up NetBoot on your server, make yourself familiar with your network configuration, including the DHCP services it provides. Be sure you meet the following requirements:

- You're the server administrator.
- You're familiar with network setup.
- You know the DHCP configuration.

You might need to work with your networking staff to change network topologies, switches, routers, and other network settings.

Client Computer Requirements

All systems supported by Mac OS X v10.6 can use NetBoot to start from a Mac OS X disk image on a server. At the time of this publication, this includes any Intel-based Macintosh computer.

You must install the latest firmware updates on all client computers. Firmware updates are available from the Apple support website: www.apple.com/support/.

Client Computer RAM Requirements

NetBoot client computers must have at least 512 MB of RAM.

Network Install client computers must also have 512 MB of RAM.

Software Updates for NetBoot System Disk Images

You must use the latest system software when creating NetBoot disk images. New Macintosh computers require updates of system software, so if you have new Macintosh clients you must update your NetBoot images.

To update a Mac OS X disk image, you must recreate the image. New images can easily be recreated by running a saved image creation workflow. For more information, see "Creating Images" on page 26.

Ethernet Support on Client Computers

NetBoot is supported only over built-in Ethernet connections. Multiple Ethernet ports are not supported on client computers. Clients must have at least 100-Mbit Ethernet adapters.

Network Hardware Requirements

The type of network connections you must use depends on the number of clients you expect to boot over the network:

- 100-Mbit Ethernet (for booting fewer than 10 clients)
- 100-Mbit switched Ethernet (for booting 10–50 clients)
- Gigabit Ethernet (for booting more than 50 clients)

These are estimates for the number of clients supported. For more details of the optimal system and network configurations to support the number of clients you have, see “Capacity Planning” on page 46.

Network Service Requirements

Depending on the types of clients you want to boot or install, your NetBoot server must also provide the following supporting services.

Service provided by NetBoot server	For booting Mac OS X computers with hard disks	For booting Mac OS X computers without hard disks
DHCP	Optional	Optional
NFS	Required if no HTTP	Required if no HTTP
AFP	Not required	Required
HTTP	Required if no NFS	Required if no NFS
TFTP	Required	Required

Note: DHCP service is listed as optional because although it is required for NetBoot it can be provided by a server other than the NetBoot server. Services marked *required* must be running on the NetBoot server.

NetBoot and AirPort

The use of AirPort wireless technology to boot clients using NetBoot is not supported by Apple and is discouraged.

Capacity Planning

The number of NetBoot client computers your server can support depends on how your server is configured, when your clients routinely start, the server’s hard disk space, and a number of other factors. When planning for your server and network needs, consider these factors:

- **Ethernet speed:** 100Base-T or faster connections are required for client computers and the server. As you add clients, you might need to increase the speed of your server’s Ethernet connections.

Ideally you want to take advantage of the Gigabit Ethernet capacity built in to your Mac OS X server hardware to connect to a Gigabit switch. From the switch, connect Gigabit Ethernet or 100-Mbit Ethernet to each NetBoot client.

- **Hard disk capacity and number of images:** Boot and installation images occupy hard disk space on server volumes, depending on the size and configuration of the system image and the number of images being stored.

Images can be distributed across multiple volumes or multiple servers. For more information, see “Performance and Load Balancing” on page 67.

- **Hard disk capacity and number of users:** If you have a large number of diskless clients, consider adding a separate file server to your network to store temporary user documents.

Because the system software for a disk image is written to a shadow image for each client booting from the disk image, you can get a rough estimate for the required hard disk capacity required by multiplying the size of the shadow image by the number of clients.

- **Number of Ethernet ports on the switch:** Distributing NetBoot clients over multiple Ethernet ports on your switch offers a performance advantage. Each port must serve a distinct segment.

Serial Number Considerations

Before starting NetBoot service, make sure you obtain a site license for the images you will serve. The license covers all NetBoot images served from a server. For every extra server, you must obtain a site license to provide NetBoot service. Contact Apple to obtain site licenses.

If you plan on serving Network Install images for installing Mac OS X and Mac OS X Server, also make sure that you have a site license.

If you plan on serving Network Install images for installing Mac OS X Server, you can use the Mac OS X Server Assistant to generate a setup file that you can add to the Network Install image so the server knows how to configure itself automatically.

If you use a generic file, you'll need to enter the serial number manually using Server Admin.

Turning NetBoot Service On

Before you can configure NetBoot settings, you must turn NetBoot service on in Server Admin.

To turn NetBoot service on:

- 1 Open Server Admin and connect to the server.
- 2 Click Settings.
- 3 Click Services.
- 4 Click the NetBoot checkbox.
- 5 Click Save.

Setting Up NetBoot Service

You set up NetBoot service by configuring the following groups of settings on the Settings pane for NetBoot service in Server Admin.

- **General.** Enable the NetBoot ports, select where images and client data resides, and set the number of AFP connections.
- **Images.** Enable images and select the default image.
- **Filters.** (Optional) Enable NetBoot and DHCP filtering to determine the hardware addresses of client computers you want to image.
- **Logging.** Choose the level of detail that is recorded in the service log.

The following sections describe the tasks for configuring these settings and how to start NetBoot service after you configure it.

Configuring NetBoot General Settings

You use General settings to enable NetBoot service on at least one port and select where image and client data resides.

To configure NetBoot General settings:

- 1 Open Server Admin and connect to the server.
- 2 Click the triangle at the left of the server.
The list of services appears.
- 3 From the expanded Servers list, select NetBoot.
- 4 Click Settings, then click General.
- 5 In the Enable column, click the checkbox next to the network ports you want to use for serving images.
- 6 In the Images column, click the checkbox to choose where to store images.
- 7 In the Client Data column, click the checkbox for each local disk volume where you want to store shadow files used by Mac OS X diskless clients.
- 8 Click Save.

Configuring Images Settings

You use Images settings to enable images and select the default image.

To configure NetBoot Images settings:

- 1 Open Server Admin and connect to the server.
- 2 Click the triangle at the left of the server.
The list of services appears.
- 3 From the expanded Servers list, select NetBoot.
- 4 Click Settings, then click Images.

- 5 Enable the images you want your clients to use, specify if they are available for diskless clients, and choose the protocol for delivering them.
If you're not sure which protocol to use, choose NFS.
- 6 In the Default column, click the checkbox to select the default image.
You must select separate default images for Intel-based and PowerPC-based Macintosh clients.
- 7 Click Save.

Configuring Filters Settings

To restrict client computers, you can set up filters that allow or deny access to NetBoot service depending on the computer's MAC address.

You can enter a MAC address as canonical or noncanonical in the filter list. The canonical form of a MAC address contains leading zeros and lowercase hex digits separated by a ":". For example, 01:a1:0c:32:00:b0 is the canonical form of a MAC address and 1:a1:c:32:0:b0 is the noncanonical form of the same MAC address.

To configure NetBoot Filters settings:

- 1 Open Server Admin and connect to the server.
- 2 Click the triangle at the left of the server.
The list of services appears.
- 3 From the expanded Servers list, select NetBoot.
- 4 Click Settings, then click Filters.
- 5 Select "Enable NetBoot/DHCP filtering."
- 6 Select "Allow only clients listed below (deny others)" or "Deny only clients listed below (allow others)."
- 7 Use the Add (+) and Delete (-) buttons to set up the list of client addresses, and click OK.

To look up a MAC address, enter the client's DNS name or IP address in the Host Name field and click Find.

To find the hardware address for a computer using Mac OS X, look on the TCP/IP pane of the computer's Network preference or run Apple System Profiler.

- 8 Click Save.

Note: You can also restrict access to a NetBoot image by selecting the name of the image in the Images pane of NetBoot service settings in Server Admin, clicking the Edit (/) button, and providing the required information.

Configuring NetBoot Logging Settings

You use Logging settings to choose the level of detail that is recorded in the service log.

To configure NetBoot Logging settings:

- 1 Open Server Admin and connect to the server.
- 2 Click the triangle at the left of the server.
The list of services appears.
- 3 From the expanded Servers list, select NetBoot.
- 4 Click Settings, then click Logging.
- 5 From the pop-up menu, choose the log detail level (Low, Medium, or High).
- 6 Click Save.

From the command line:

- To configure a NetBoot service setting:

```
$ sudo serveradmin settings netboot:logging_level = value
```

- To view NetBoot service configuration settings:

```
$ sudo serveradmin settings netboot
```

Parameter	Description
logging_level	Default = Medium Possible values are Low, Medium, or High.

For information about command-line parameters, see “NetBoot Service Settings” on page 95. For information about `serveradmin`, see its man page. For the basics of command-line tool usage, see *Introduction to Command-Line Administration*.

Enabling NetBoot 1.0 for Older NetBoot Clients

If you want older computers, such as tray-loading iMac or Power Macintosh G3 (Blue and White) computers, to use NetBoot, you must enable NetBoot 1.0. You can do so by using the `dscl` tool.

Note: NetBoot 1.0 and 2.0 can run on the same network simultaneously.

To enable NetBoot:

```
$ sudo dscl . create /config/dhcp old_netboot_enabled port_list
$ sudo killall bootpd
```

Parameter	Description
port_list	List of ports you want to enable for NetBoot 1.0, formatted like <code>en0 en1 en2</code> .

Starting NetBoot and Related Services

NetBoot service uses AFP, NFS, DHCP, Web, and TFTP services, depending on the types of clients you're trying to boot (see "Network Service Requirements" on page 46). You can use Server Admin to start AFP, DHCP, Web, and NetBoot services. NFS and TFTP services start automatically.

To start NetBoot service:

- 1 Open Server Admin and connect to the server.
- 2 Click the triangle at the left of the server.
The list of services appears.
- 3 If you'll be booting diskless Mac OS X clients, start AFP service by selecting AFP in the Servers list and clicking the Start AFP button (below the Servers list).
- 4 If your server is providing DHCP service, make sure the DHCP service is configured and running; otherwise, DHCP service must be supplied by another server on your network.
If your NetBoot server is also supplying DHCP service, you might get better performance if you configure your server as a gateway. That is, configure your subnets to use the server's IP address as the router IP address.
- 5 From the expanded Servers list, select NetBoot.
- 6 Click Settings, then click General.
- 7 Select which network ports to use for providing NetBoot service.
You can select one or more network ports to serve NetBoot images. For example, if you have a server with two network interfaces, each connected to a network, you can choose to serve NetBoot images on both networks.
- 8 Click Images.
- 9 Select the images to serve.
- 10 Click Save.
- 11 Click the Start NetBoot button (below the Servers list).

From the command line:

- To start NetBoot and supporting services:

```
$ sudo serveradmin start netboot
```

If you get the following response, you have not yet enabled NetBoot on a network port:

```
$ netboot:state = "STOPPED"
$ netboot:status = 5000
```

For information about `serveradmin`, see its man page. For the basics of command-line tool usage, see *Introduction to Command-Line Administration*.

Managing Images

After you set up NetBoot service, you can use Server Admin and System Image Utility to customize and manage images for your network environment.

Enabling Images

You must enable disk images on your server to make the images available to client computers for NetBoot startups.

To enable disk images:

- 1 Open Server Admin and connect to the server.
- 2 Click the triangle at the left of the server.
The list of services appears.
- 3 From the expanded Servers list, select NetBoot.
- 4 Click Settings, then click Images.
- 5 For each image you want your clients to see, click the checkbox in the Enable column.
- 6 Click Save.

From the command line:

- To enable disk images:

```
$ sudo serveradmin settings netboot:netBootImagesRecordsArray:_array_
index:n:IsEnabled = yes
```

Parameter	Description
netBootImagesRecordsArray:_array_ index:<n>:IsEnabled	Default = no Sets whether the image is available to NetBoot.
<i>n</i>	Specifies the array index number of the volume you want to set as the default image.

For information about command-line parameters, see “NetBoot Service Settings” on page 95. For information about `serveradmin`, see its man page. For the basics of command-line tool usage, see *Introduction to Command-Line Administration*.

Choosing Where Images Are Stored

You can use Server Admin to choose volumes to use for storing NetBoot and NetInstall images.

WARNING: Don't rename a NetBoot share point or the volume it resides on. Don't use Server Admin to stop sharing for a NetBoot share point unless you first deselect the share point for images and shadow files.

To choose volumes for storing image files:

- 1 Open Server Admin and connect to the server.
- 2 Click the triangle at the left of the server.
The list of services appears.
- 3 From the expanded Servers list, select NetBoot.
- 4 Click Settings, then click General.
- 5 In the list of volumes (in the lower half of the pane), click the checkbox in the Images column for each volume you want to store image files on.
- 6 Click Save.

From the command line:

- To specify a volume to store image files:

```
$ sudo serveradmin settings
netboot:netBootStorageRecordsArray:_array_index:n:sharepoint = value
netboot:netBootStorageRecordsArray:_array_index:n:clients = value
netboot:netBootStorageRecordsArray:_array_index:n:ignorePrivs = value
netboot:netBootStorageRecordsArray:_array_index:n:volType = value
netboot:netBootStorageRecordsArray:_array_index:n:path = value
netboot:netBootStorageRecordsArray:_array_index:n:volName = value
netboot:netBootStorageRecordsArray:_array_index:n:volIcon = value
netboot:netBootStorageRecordsArray:_array_index:n:okToDeleteClients =
    value
netboot:netBootStorageRecordsArray:_array_index:n:okToDeleteSharepoint =
    value
Control-D
```

Parameter (netboot:)	Description
netBootStorageRecordsArray:_array_index:<n>:sharepoint	First parameter in an array describing a volume available to serve images. Default = "no"
netBootStorageRecordsArray:_array_index:<n>:clients	Default = "no"
netBootStorageRecordsArray:_array_index:<n>:ignorePrivs	Default = "false"
netBootStorageRecordsArray:_array_index:<n>:volType	Default = <voltype> Example: "hfs"
netBootStorageRecordsArray:_array_index:<n>:path	Default = "/"
netBootStorageRecordsArray:_array_index:<n>:volName	Default = <name>

Parameter (netboot:)	Description
netBootStorageRecordsArray:_array_ index:<n>:volIcon	Default = <icon>
netBootStorageRecordsArray:_array_ index:<n>:okToDeleteClients	Default = "yes"
netBootStorageRecordsArray:_array_ index:<n>:okToDeleteSharepoint	Default = "yes"
<i>n</i>	The array index number of the volume you want to set as the default image.

For information about `serveradmin`, see its man page. For the basics of command-line tool usage, see *Introduction to Command-Line Administration*.

Choosing Where Shadow Files Are Stored

When a diskless client boots, temporary (shadow) files are stored on the server. You can use Server Admin to specify which server volumes are used to store the temporary files.

WARNING: Don't rename a NetBoot share point or the volume it resides on. Don't use Server Admin to stop sharing for a NetBoot share point unless you first deselect the share point for images and shadow files.

To use a volume for storing shadow files:

- 1 Open Server Admin and connect to the server.
- 2 Click the triangle at the left of the server.
The list of services appears.
- 3 From the expanded Servers list, select NetBoot.
- 4 Click Settings, then click General.
- 5 In the list of volumes (in the lower half of the pane), click the checkbox in the Client Data column for the volumes you want to store shadow files on.
- 6 Click Save.

From the command line:

- To specify a volume to store shadow files on:

```
$ sudo serveradmin settings
netboot:netBootStorageRecordsArray:_array_index:n:sharepoint = value
netboot:netBootStorageRecordsArray:_array_index:n:clients = yes
netboot:netBootStorageRecordsArray:_array_index:n:ignorePrivs = value
netboot:netBootStorageRecordsArray:_array_index:n:volType = value
netboot:netBootStorageRecordsArray:_array_index:n:path = value
```

```

netboot:netBootStorageRecordsArray:_array_index:n:volName = value
netboot:netBootStorageRecordsArray:_array_index:n:volIcon = value
netboot:netBootStorageRecordsArray:_array_index:n:okToDeleteClients =
    value
netboot:netBootStorageRecordsArray:_array_index:n:okToDeleteSharepoint =
    value
Control-D

```

Parameter (netboot:)	Description
netBootStorageRecordsArray:_array_index:<n>:sharepoint	First parameter in an array describing a volume available to serve images. Default = "no"
netBootStorageRecordsArray:_array_index:<n>:clients	Default = "no"
netBootStorageRecordsArray:_array_index:<n>:ignorePrivs	Default = "false"
netBootStorageRecordsArray:_array_index:<n>:volType	Default = <voltype> Example: "hfs"
netBootStorageRecordsArray:_array_index:<n>:path	Default = "/"
netBootStorageRecordsArray:_array_index:<n>:volName	Default = <name>
netBootStorageRecordsArray:_array_index:<n>:volIcon	Default = <icon>
netBootStorageRecordsArray:_array_index:<n>:okToDeleteClients	Default = "yes"
netBootStorageRecordsArray:_array_index:<n>:okToDeleteSharepoint	Default = "yes"
<i>n</i>	The array index number of the volume you want to set as the default image.

For information about `serveradmin`, see its man page. For the basics of command-line tool usage, see *Introduction to Command-Line Administration*.

Using Images Stored on Remote Servers

You can store NetBoot or NetInstall images on separate remote servers other than the NetBoot server. You must copy the images from the NetBoot server to the remote server and then configure the remote server to use the images.

To store an image on a separate remote server:

- 1 Copy the `image.nbi` folder from the NetBoot server to the remote server on a NetBoot sharepoint (`/Library/NetBoot/NetBootSPn`).

If the image is on the remote server, you can create the .nbi folder on the NetBoot server by duplicating an existing .nbi folder and adjusting the values in its NBImageInfo.plist file.

- 2 Open Server Admin and connect to the remote server.
- 3 Click the triangle at the left of the server.
The list of services appears.
- 4 From the expanded Servers list, select NetBoot.
- 5 Click Settings, then click Images.
- 6 For each image you want your clients to see from the remote server, click the checkbox in the Enable column.
- 7 Select the protocol you want NetBoot to use when serving your image (NFS or HTTP).
- 8 Click Save.

Specifying the Default Image

The default image is the image used when you start up a client computer while holding down the N key, providing that the client hasn't selected a NetBoot or NetInstall volume via Startup Disk. See "Starting Up Using the N Key" on page 62.

If you've created more than one startup disk image, you can use NetBoot service settings in Server Admin to select the default startup image.

Important: If you have diskless clients, set their boot image as the default image.

If you have more than one NetBoot server on the network, a client uses the default image from the first server that responds. There is no way to control which default image is used when more than one is available.

To specify the default boot image:

- 1 Open Server Admin and connect to the server.
- 2 Click the triangle at the left of the server.
The list of services appears.
- 3 From the expanded Servers list, select NetBoot.
- 4 Click Settings, then click Images.
- 5 In the Default column, click the checkbox next to the image.
You can select separate default images for Intel-based and PowerPC-based Macintosh computers. The architecture column shows the image type. Mac OS X v10.6 images can boot Intel-based Macintosh computers only.
- 6 Click Save.

From the command line:

- To specify the default image:

```
$ sudo serveradmin settings netboot:netBootImagesRecordsArray:_array_
    index:n:IsDefault = yes
```

Parameter (netboot:)	Description
netBootImagesRecordsArray:_array_ index:<n>:IsDefault	yes Specifies this image file as the default boot image on the subnet.
<i>n</i>	Specifies the array index number of the volume you want to set as the default image.

For information about `serveradmin`, see its man page. For the basics of command-line tool usage, see *Introduction to Command-Line Administration*.

Setting an Image for Diskless Booting

You can use Server Admin to make an image available for booting client computers that have no local disk drives. Setting an image for diskless booting instructs the NetBoot server to allocate space for the client's shadow files.

To make an image available for diskless booting:

- 1 Open Server Admin and connect to the server.
- 2 Click the triangle at the left of the server.
The list of services appears.
- 3 From the expanded Servers list, select NetBoot.
- 4 Click Settings, then click Images.
- 5 In the Diskless column, click the box next to the image in the list.
- 6 Click Save.

Important: If you have diskless clients, set their NetBoot image as the default image.

For help specifying where the client's shadow files are stored, see "Choosing Where Shadow Files Are Stored" on page 54.

From the command line:

- To set an image for a diskless boot:

```
$ sudo serveradmin settings netboot:netBootImagesRecordsArray:_array_
    index:n:SupportsDiskless = yes
```

Parameter (netboot:)	Description
<code>netBootImagesRecordsArray:_array_ index:<n>:SupportsDiskless</code>	yes Directs the NetBoot server to allocate space for shadow files needed by diskless clients.
<code>n</code>	Specifies the array index number of the volume you want to set as the default image.

For information about `serveradmin`, see its man page. For the basics of command-line tool usage, see *Introduction to Command-Line Administration*.

Restricting NetBoot Clients by Filtering Addresses

The filtering feature of NetBoot service lets you restrict access to the service based on the client's Ethernet hardware (MAC) address. A client's hardware address is added to the filter list the first time it starts from an image on the server and is permitted access by default, so it is usually not necessary to enter hardware addresses manually.

To restrict client access to NetBoot service:

- 1 Open Server Admin and connect to the server.
- 2 Click the triangle at the left of the server.
The list of services appears.
- 3 From the expanded Servers list, select NetBoot.
- 4 Click Settings, then click Filters.
- 5 Select "Enable NetBoot/DHCP filtering."
- 6 Select "Allow only clients listed below (deny others)" or "Deny only clients listed below (allow others)."
- 7 Use the Add (+) and Delete (-) buttons to set up the list of client addresses, and click OK.

To look up a MAC address, enter the client's DNS name or IP address in the Host Name field and click Find.

To find the hardware address for a computer using Mac OS X, look on the TCP/IP pane of the computer's Network preference or run Apple System Profiler.

- 8 Click Save.

Note: You can also restrict access to a NetBoot image by selecting the name of the image in the Images pane of NetBoot service settings in Server Admin, clicking the Edit (/) button, and providing the required information.

From the command line:

- To enable disk images:

```
$ sudo serveradmin settings
netboot:netBootFiltersRecordsArray:_array_index:n:hostName = value
netboot:netBootFiltersRecordsArray:_array_index:n:filterType = value
netboot:netBootFiltersRecordsArray:_array_index:n:hardwareAddress =
    value
Control-D
```

Parameter (netboot:)	Description
netBootFiltersRecordsArray:_array_index:<n>:hostName	The host name of the filtered computer, if available.
netBootFiltersRecordsArray:_array_index:<n>:filterType	Whether the specified computer is allowed or denied access. Options: "allow" "deny"
netBootFiltersRecordsArray:_array_index:<n>:hardwareAddress	The Ethernet hardware (MAC) address of the filtered computer.
<i>n</i>	The array index number of the volume you want to set as the default image.

For information about command-line parameters, see "NetBoot Service Settings" on page 95. For information about `serveradmin`, see its man page. For the basics of command-line tool usage, see *Introduction to Command-Line Administration*.

Setting Up NetBoot Service Across Subnets

A network boot starts when the client computer broadcasts for computers that will respond to Boot Service Discovery Protocol (BSDP). By default, routers are usually configured to block broadcast traffic to reduce the amount of unnecessary data flowing to other parts of the network.

To provide NetBoot service across subnets, you must configure the router to pass on BSDP traffic to the NetBoot server. To see if your router is capable of passing BSDP traffic, check with your router manufacturer. Sometimes this is also referred to as using a DHCP helper or a DHCP relay agent.

Setting Up Clients to Use NetBoot and NetInstall Images

4

Use this chapter to set up client computers to start or install software from images on a server.

After NetBoot service and images are configured on the server, you must set up the client computers to access and use the images.

Setting Up Diskless Clients

NetBoot service enables you to configure client computers without locally installed operating systems or even without installed disk drives. Systemless or diskless clients can start from a NetBoot server using the N key method. (See “Starting Up Using the N Key” on page 62.)

After the client computer starts, you can use Startup Disk preferences to select the NetBoot disk image as the startup disk for the client. That way you no longer need to use the N key method to start the client from the server.

Removing the system software from client computers gives you more control over user environments. By forcing the client to start up from the server and using client management to deny access to the client computer local hard disk, you can prevent users from saving files to the local hard disk.

Selecting a NetBoot Boot Image

If your computer is running Mac OS X v10.2 or later, you use Startup Disk preferences to select a NetBoot boot image.

To select a NetBoot startup image from Mac OS X:

- 1 In System Preferences, select Startup Disk.
- 2 Select the network volume you want to start the computer with.
- 3 Click Restart.

The NetBoot icon appears and the computer starts from the selected image.

From the command line:

- To select a NetBoot startup image:

```
> setenv boot-file enet:YourServerIPAddress,NetBoot\NetBootsSP*\<name
  of .nbi folder>\mach.macosx
> setenv boot-args rp=nfs: YourServerIPAddress:/private/tftpboot/
  NetBoot/NetBootSP*:<name of .nbi folder>/<Name of image>.dmg
> setenv boot-device enet: YourServerIPAddress,NetBoot\NetBootSP*\<name
  of .nbi folder>\booter
> mac-boot
```

- To choose a boot device:

```
$ sudo systemsetup -setstartupdisk /volume/Disk\ 2/System/Library/
  CoreServices
```

Parameter	Description
<i>volume</i>	The path to the boot device.
<i>Disk\ 2</i>	The name of the boot device.

For information about `systemsetup`, see its man page. For the basics of command-line tool usage, see *Introduction to Command-Line Administration*.

Imaging Multiple Clients Using the Multicast `asr` Command

You can enable a multicast image server using the Mac OS X Server Multicast `asr` command. Multicast `asr` can restore multiple clients simultaneously from one looping multicast of an `asr` disk image.

Each client can receive the restore image at any time during a multicast of the image, and the client continues receiving the first part of the next multicast until the client receives the complete restore image.

The server multicasts only one copy of the restore image at a time, and all clients receive this copy.

If the server finishes multicasting the restore image and a client is still requesting the image, the server multicasts the image again. Thus, using multicast `asr` to stream images to multiple clients doesn't congest the network nearly as much as Network Install with multiple clients.

To enable the image server, use the `asr` tool with the `-server` flag and a correctly built image and plist file.

To start a multicast server for a specified image:

```
$ asr -source <compressedimage> -server <configuration.plist>
```

The image does not start multicasting on the network until a client attempts to start a restore. The server continues to multicast the image until the process is terminated.

To configure a client to receive a multicast stream:

```
$ sudo asr -source asr://<hostname> -target <targetvol> -erase
```

The client receives the multicast stream from <hostname> and saves it to the client. To overwrite an existing image, add `-erase`. Using `-erase` with `-target` indicates an image should be overwritten when doing a multicast.

Selecting a NetInstall Image

If your computer is running Mac OS X v10.2 or later, you use Startup Disk preferences to select a NetInstall image.

To select a NetInstall image from Mac OS X:

- 1 In System Preferences, select Startup Disk.
- 2 Select the network volume you want to start the computer with.
- 3 Click Restart.

The NetBoot icon appears, the computer starts from the selected image, and the installer runs.

Starting Up Using the N Key

You can use this method to start up any supported client computer from a NetBoot disk image. When you start up with the N key, the client computer starts up from the default NetBoot disk image. If multiple servers are present, the client starts up from the default image of the first server to respond.

Note: For more information about using the N key when starting the system, see the manual that was provided with the computer. Some computers have extra capabilities.

If an older client computer that BootP for IP addressing (such as a tray-loading iMac, blue and white PowerMac G3, or older computer), use this method for starting up from a NetBoot disk image. Older computers don't support selecting a NetBoot startup disk image from the Startup Disk control pane or preferences pane.

The N key also provides a way to start up client computers that don't have system software installed. See "Setting Up Diskless Clients" on page 60.

To start from a NetBoot disk image using the N key:

- 1 Hold the N key down on the keyboard until the NetBoot icon appears in the center of the screen, then turn on (or restart) the client computer.
- 2 If a login window appears, enter your name and password.

The network disk image has an icon typical of server volumes.

Changing How NetBoot Clients Allocate Shadow Files

By default, a Mac OS X NetBoot client places its shadow files in a NetBootClients n share point on the server, where n is the share point number. If no such share point is available, the client tries to store its shadow files on a local hard disk.

For Mac OS X v10.3 and later images set for diskless booting, you can change this behavior by using a text editor to specify a value for the `NETBOOT_SHADOW` variable in the image `/etc/hostconfig` file.

These values are permitted:

Value of <code>NETBOOT_SHADOW</code>	Client shadow file behavior
<code>-NETWORK-</code>	(Default) Try to use a server NetBootClients n share point for storing shadow files. If no server share point is available, use a local drive.
<code>-NETWORK_ONLY-</code>	Try to use a server NetBootClients n share point for storing shadow files. If no server share point is available, don't boot.
<code>-LOCAL-</code>	Try to use a local drive for storing shadow files. If no local drive is available, use a server NetBootClients n share point.
<code>-LOCAL_ONLY-</code>	Try to use a local drive for storing shadow files. If no local drive is available, don't boot.

Note: This value is set in the `/etc/hostconfig` file in the image .dmg file, not in the server `hostconfig` file.

Managing NetBoot Service

5

Use this chapter to learn about daily tasks that keep NetBoot service running efficiently, and to learn about load balancing across multiple volumes on a server or across multiple servers.

You can manage NetBoot service using Server Admin. Server Admin enables you to verify the overall status of the connection, to review logs, to control clients, and to manage boot and installation images. You can use System Image Utility to distribute boot images across servers for load balancing.

Controlling and Monitoring NetBoot

The following sections show how to stop NetBoot service, disable images, and monitor or restrict clients.

Turning Off NetBoot Service

The best way to prevent clients from using NetBoot on the server is to disable NetBoot service on all Ethernet ports.

To stop NetBoot:

- 1 Open Server Admin and connect to the server.
- 2 Click the triangle at the left of the server.
The list of services appears.
- 3 From the expanded Servers list, select NetBoot.
- 4 Click the Stop NetBoot button (below the Servers list) and perform one of the following tasks:
 - To stop service on a specific Ethernet port, click Settings, click General, and deselect the Enable checkbox for the port.
 - To stop serving a specific image, click Settings, click Images, and deselect the Enable checkbox for the image.

- To stop service to a client, click Settings, click Filters, select Enable NetBoot Filtering, choose “Deny only clients listed below,” and add the client’s hardware address to the list.

From the command line:

- To stop NetBoot service or disable images:

```
$ sudo serveradmin stop netboot
```

For information about `serveradmin`, see its man page. For the basics of command-line tool usage, see *Introduction to Command-Line Administration*.

Disabling a Boot or Installation Image

Disabling an image prevents client computers from starting using the image.

To disable a NetBoot disk image:

- 1 Open Server Admin and connect to the server.
- 2 Click the triangle at the left of the server.
The list of services appears.
- 3 From the expanded Servers list, select NetBoot.
- 4 Click Settings, then click Images.
- 5 In the Enable column, deselect the checkbox for the image.
- 6 Click Save.

From the command line:

- To stop NetBoot service or disable images:

```
$ sudo serveradmin stop netboot
```

For information about `serveradmin`, see its man page. For the basics of command-line tool usage, see *Introduction to Command-Line Administration*.

Viewing a List of NetBoot Clients

You can use Server Admin to see a list of clients that have booted from the server.

To view the client list:

- 1 Open Server Admin and connect to the server.
- 2 Click the triangle at the left of the server.
The list of services appears.
- 3 From the expanded Servers list, select NetBoot.
- 4 Click Clients.
- 5 To update the list, click the Refresh button (below the Servers list).

Note: This is a cumulative list—a list of all clients that have connected—not a list of connected clients. The last boot time is shown for each client.

Viewing a List of NetBoot Connections

You can use Server Admin to see a list of clients that are booted from the server. NetInstall clients display install progress information.

To view the NetBoot connections list:

- 1 Open Server Admin and connect to the server.
- 2 Click the triangle at the left of the server.
The list of services appears.
- 3 From the expanded Servers list, select NetBoot.
- 4 Click Connections.
- 5 To update the list, click the Refresh button (below the Servers list).

Checking the Status of NetBoot and Related Services

You can use Server Admin to check the status of NetBoot service and the services (such as NFS and HTTP) it uses.

To check NetBoot service status:

- 1 Open Server Admin and connect to the server.
- 2 Click the triangle at the left of the server.
The list of services appears.
- 3 From the expanded Servers list, select NetBoot.
- 4 Click Overview to see if the service is running, when the last client update occurred, and which related services are running for an image type.
- 5 To review the event log, click Log.
- 6 To see a list of NetBoot clients that have booted from the server, click Clients.
- 7 To see a list of connected users, click Connections.

The list includes the client computer name, IP address, the percentage complete, and the status.

From the command line:

- To see if the service is running:

```
$ sudo serveradmin status netboot
```
- To see the complete service status:

```
$ sudo serveradmin fullstatus netboot
```

For information about `serveradmin`, see its man page. For the basics of command-line tool usage, see *Introduction to Command-Line Administration*.

Viewing the NetBoot Service Log

You can use Server Admin to view a log containing diagnostic information.

To view the NetBoot service log:

- 1 Open Server Admin and connect to the server.
- 2 Click the triangle at the left of the server.
The list of services appears.
- 3 From the expanded Servers list, select NetBoot.
- 4 Click Log, then use the Filter field to search for specific entries.

From the command line:

- To view the latest entries in a log:

```
$ tail log-file
```

- To see where service logs are located:

```
$ sudo serveradmin command netboot:command = getLogPaths
```

For information about `tail` and `serveradmin`, see their man pages. For the basics of command-line tool usage, see *Introduction to Command-Line Administration*.

Performance and Load Balancing

For good startup performance, the NetBoot server must be available to the client computer relying on it. To provide responsive and reliable NetBoot service, set up multiple NetBoot servers in your network.

Many sites using NetBoot service achieve acceptable responsiveness by staggering the boot times of client computers to reduce network load. Generally, it isn't necessary to boot client computers at the same time; rather, client computers are booted early in the morning and remain booted throughout the work day.

You can program staggered startup times using the Energy Saver preferences pane.

Load Balancing NetBoot Images

If heavy usage and simultaneous client startups are overloading a NetBoot server and causing delays, consider load balancing by adding extra NetBoot servers to distribute the demands of the client computers across multiple servers.

When incorporating multiple NetBoot servers, use switches in your network infrastructure. The shared nature of hubs creates a single shared network on which extra servers must vie for time.

Distributing NetBoot Images Across Servers

If you set up more than one NetBoot server on your network, you can place copies of a specific NetBoot image on multiple servers to distribute the load. By assigning the copies the same image index ID in the range 4096–65535, you can advertise them to your clients as a single image to avoid confusion.

Note: You must customize the image by creating a workflow with the Create Image action to assign the image an index ID.

To distribute an image across servers:

- 1 Locate the image file on the server where the original image is stored.
- 2 If the image index ID is 4095 or lower, recreate the image and modify the index ID using the Create Image action in a workflow, then assign the image an index ID in the range 4096–65535.

For more information, see “Assembling Workflows” on page 38.

The image ID can be changed from Server Admin by double-clicking the Image ID field and entering the new ID.

- 3 Create copies or move image files to other servers.
- 4 On each server, use Server Admin to enable the image for NetBoot service.

Clients still see the image listed only once in Startup Disk preferences, but the server that delivers its copy of the image is selected based on server activity.

Smaller improvements can be achieved by distributing NetBoot images across multiple disk drives on a single server. For high-performance disk storage, consider using an Xserve RAID or Xsan volume to store the images on.

Distributing NetBoot Images Across Server Disk Drives

Even with a single NetBoot server, you might improve performance by distributing copies of an image across multiple disk drives on the server. By assigning the copies the same image index ID in the range 4096–65535, you can advertise them to your clients as a single image.

Important: Don’t distribute images across different partitions of the same physical disk drive. Doing so does not improve, and can even reduce, performance.

To distribute an image across disk drives:

- 1 Open Server Admin and connect to the server.
- 2 Click the triangle at the left of the server.
The list of services appears.
- 3 From the expanded Servers list, select NetBoot.
- 4 Click Settings, then click General.

- 5 In the Images column, select the checkbox for each volume you want to store images on.
Choose volumes on different physical disk drives.
- 6 Click Save, then click Images.
- 7 If the image's index is 4095 or lower, double-click the ID, enter an index in the range 4096–65535, and save the change.
- 8 Open Terminal and use the `scp` secure copy tool to copy the image to the NetBootSPn share points on the other volumes.

For example:

```
$ scp /Library/NetBoot/NetBootSP0/image.nbi [admin_name]@[ip_address]:/  
Volumes/Drive2/Library/NetBoot/NetBootSP1
```

where `[admin_name]` is an admin login and `[ip_address]` is the correct IP address for that server.

You are prompted for the password of the admin login you supply.

Balancing NetBoot Image Access

If you add a second NetBoot server to a network, have your users reselect their NetBoot image in the Startup Disk control pane or preferences pane. This causes the NetBoot server load to be redistributed among the servers.

You can also force redistribution of the load by deleting the `/var/db/bsdpd_clients` file from the existing NetBoot server.

Note: After deleting the `bsdpd_clients` file, the server does not remember which clients selected which NetBoot or NetInstall volumes via Startup Disk. Unless the clients reselect their intended NetBoot or NetInstall volumes, the clients will boot into the default image on the server.

Similarly, if you're recovering from a server or infrastructure failure and your clients have been starting up from a reduced number of NetBoot servers, delete the `bsdpd_clients` file from the running servers so clients can again start from among the entire set of servers.

The `bsdpd_clients` file holds the Ethernet MAC addresses of the computers that have selected the server as their NetBoot server.

As long as a client has an entry in an available server's `bsdpd_clients` file, it always starts from that server. If that server becomes unavailable, the clients locate and associate themselves with an available server until you remove their entries (or the files) from their servers.

Note: If a client is registered on more than one server because an unavailable server comes back on line, the client starts up from the server with the fewest number of clients that started from it.

Distributing Shadow Files

Clients starting up from Mac OS X diskless images store temporary (shadow) files on the server.

By default, NetBoot for Mac OS X clients creates a share point for client shadow files on the server boot volume. (You can change this behavior. See “Choosing Where Shadow Files Are Stored” on page 54.)

You can use Server Admin to see this share point and to add others. The share points are named NetBootClients n where n is the share point number.

Share points are numbered starting with zero. For example, if your server has two disk volumes, the default shadow-file folder is NetBootClients0 on the boot volume. If you use Server Admin to specify that client data will also be stored on the second volume, the folder is named NetBootClients1. NetBoot stores the first client’s shadow files on NetBootClients0, the second client’s shadow files on NetBootClients1, the third client’s shadow files on NetBootSP0, and so on.

Likewise, with three volumes and eight clients, the first, fourth, and seventh clients use the first volume; the second, fifth, and eighth clients use the second volume; and the third and sixth clients use the third volume. This load balancing is automatic and usually provides optimal performance.

To prevent shadow files from being placed on a specific volume, use the NetBoot Service General settings in Server Admin. Deselect the client data checkbox for any volume you don’t want shadow files placed in.

You can also prevent shadow files from being placed on a specific volume or partition by deleting the hidden file /Library/NetBoot/.clients, which is a symbolic link, and then stopping and restarting NetBoot service.

Solving System Imaging Problems

6

Use this chapter to find solutions for common problems you might encounter while working with NetBoot and NetInstall.

This chapter contains solutions to common system imaging problems.

General Tips

- Make sure a DHCP service is available on your network. It can be provided by the Mac OS X Server DHCP service or another server.
- Make sure required services are started on the server. See “Network Service Requirements” on page 46. Open Server Admin and verify the following:
 - If you’re booting Mac OS X diskless clients, AFP is started
 - If you’re using HTTP instead of NFS to deliver images, Web service is started

If NetBoot Client Computers Won’t Start

If your NetBoot client computers will not start:

- Sometimes a computer might not start immediately because other computers are putting a heavy demand on the network. Wait a few minutes and try starting again.
- Make sure cables are properly connected and that the computer and server are getting power.
- If you installed memory or an expansion card in the client computer, make sure it is installed properly.
- If the computer has a local hard disk with a System Folder on it, disconnect the Ethernet cable and try to start the computer from the local hard disk, then reconnect the Ethernet cable and try to start the computer from the network.
- Boot the client computer from a local disk and verify that it is getting an IP address from DHCP.
- On a diskless or systemless client, start from a system CD and use Startup Disk preferences to select a boot image.

If You Want to Change the Image Name

You can't edit the name of an image with System Image Utility after you create it. However, there are other ways to change the name, as shown in the following sections.

Changing the Name of an Uncompressed Image

This section describes how to change the name of an uncompressed image that you created using System Image Utility.

To change the name of an uncompressed image:

- 1 Mount the image in Finder by opening the `.nbi` folder containing the image and double-clicking it.

- 2 Open Terminal and enter the following command to rename the image:

```
$ sudo diskutil rename /Volumes/image new_name
```

Replace *image* with the name of the image you want to rename and *new_name* with the new name of the image.

- 3 When prompted, enter your administrator password.

The name of the image changes.

- 4 Unmount the image.
- 5 Remount the image to verify that it has been renamed.

Changing the Name of a Compressed Image

This section describes how to change the name of a compressed image that you created using System Image Utility.

To change the name of a compressed image:

- 1 Mount the image in Finder by opening the `.nbi` folder containing the image and double-clicking it.

- 2 Open Disk Utility.

- 3 Select the image and click Convert.

- 4 In the Save As field, enter a name.

- 5 Select a different location to save the image to.

For example, save the image on the Desktop folder.

- 6 From the Image Format menu, choose read/write.

- 7 Click Save.

- 8 Unmount the image.

- 9 Mount the new image in the Finder.

- 10 Open a Terminal window and enter the following to rename the image:

```
$ sudo diskutil rename /Volumes/image new_name
```

Replace *image* with the name of the image you want to rename and *new_name* with the new name of the image.

- 11 When prompted, enter your administrator password.
The name of the image changes.
- 12 Unmount the image.
- 13 Remount the image to verify that the image has been renamed.
- 14 Unmount the image.
- 15 Remove the original image from the .nbi folder and store it somewhere else.
- 16 In Disk Utility, select the new image and click Convert.
- 17 Give the image the same name as the one it had inside the .nbi folder.
- 18 In the Where field, select the .nbi folder.
- 19 From the Format menu, choose Compressed.
- 20 Click Save.
- 21 Test the new image to make sure it mounts properly.
- 22 Discard the old image.

Part II: Software Update Administration



The chapters in this part of the guide introduce you to Software Update and the applications and tools available for administering Software Update.

Chapter 7	Understanding Software Update Administration
Chapter 8	Setting Up Software Update
Chapter 9	Managing Software Update
Chapter 10	Solving Software Update Problems

Understanding Software Update Administration

7

Use this chapter to learn how to use Software Update to update Apple software on your network.

Software Update offers you ways to manage Macintosh software updates from Apple on your network. In an uncontrolled environment, users might connect to Apple Software Update servers at any time and update their computers with software that is not approved by your IT group.

Using local Software Update servers, your client computers access only the software updates you permit from software lists that you control, improving your ability to manage computer software updates. For example you can:

- Download software updates from the Apple Software Update servers to a local server for sharing with local network clients and reduce the amount of bandwidth used outside your enterprise network.
- Direct users, groups, and computers to specific local Software Update servers using managed preferences.
- Manage the software update packages users can access by enabling and disabling packages at the local server.
- Mirror updates between Apple Software Update servers and your server to make sure you have the most current updates.

Note: Software Update does not update software on the server. For information about keeping your server software current, see *Advanced Server Administration*.

Note: You can't use Software Update to provide third-party software updates.

Inside the Software Update Process

This section describes how Software Update servers are implemented on Mac OS X, including information about the protocols, files, folder structures, and configuration details.

Overview

The process that starts Software Update is `SoftwareUpdateServer`. When you start Software Update, it contacts Apple's Software Update server and requests a list of available software to download locally.

You can to *copy* (store packages locally) and *enable* (make the packages available to users) any files in the list. You can also limit user bandwidth for updates and choose to automatically copy and enable newer updates from the Apple server.

Note: Software Update stores its configuration information in the file `/etc/swupd/swupd.conf`.

Catalogs

Software Update supports only `pkm.en` file types, recognized only by Mac OS X v10.4 and later. As you copy updates on your server, your server will download and store update packages in the `/usr/share/swupd/html/` folder.

Although this path is static and can't be modified to store the packages in an alternate location, you can change the URL to access a different server.

Note: This version of Mac OS X Server supports only Apple-specific software packages for use with your update server. Modified Apple and third-party update software packages cannot be shared.

After packages are copied locally, you can enable them for users to update their software. Mac clients running Software Update see only enabled packages in the list of available software for their computer.

Software packages removed from the Apple published catalog are also removed from the software catalog on your local server, making those packages unavailable for download by client systems configured to use the local Software Update service.

Installation Packages

When Software Update starts, your Software Update server receives a list of available software updates from the Apple Software Update service. Your server synchronizes the contents of the software catalog with Apple's Software Update server when you restart your server or when you enter the following command:

```
$ /usr/local/bin/swupd_syncd
```

To manually update the catalog, select the Refresh button in the Updates pane of Software Update settings.

Changes in the Apple published catalog are immediately reflected on your local server. Software packages removed from the Apple published catalog are also removed from the software catalog on your local server, making those packages unavailable for further download by client systems configured to use the local Software Update service.

Staying Up-To-Date with the Apple Server

To keep your service synchronized with the most current information, your Software Update server must always remain in contact with the Apple server. Software Update service regularly checks with an Apple Software Update to update usage information and send lists of newly available software to the updates catalog on your server as they become available.

The Apple Software Update server uses the `swupd_syncd` synchronization daemon to determine the time between updates to your server and to make sure the latest update packages are available.

Limiting User Bandwidth

Software Update lets you limit the bandwidth that client computers can use when downloading software updates from your Software Update server.

Setting a limit on the bandwidth enables you to control traffic on your network and prevents Software Update clients from slowing the network. For example, if you limit the bandwidth to 56 Kbps, each software update client can download updates at 56 Kbps. If five clients connect simultaneously to the server, the total bandwidth used by the clients will be 280 Kbps (56 Kbps x 5).

Revoked Files

On a rare occasion Apple might provide a software update and want to revoke or deprecate a package from circulation.

If Apple revokes the update package, the package is removed from your catalog and stored packages. If Apple deprecates an update package, it is removed from your catalog but remains in your stored packages until you remove it.

In either case the packages are irrevocably removed from the catalog and are no longer available to enable or publish to clients using Software Update.

Software Update Package Format

You can't make your own Software Update packages. For security considerations and to protect from attackers faking packages, the Software Update package installer won't install a package unless it is signed by Apple.

In addition, Software Update works only with the new package format supported in Mac OS X Server v10.4 or later.

Log Files

The log file for the Software Update server is `/Library/Logs/SoftwareUpdateServer.log`. This log file records Software Update events as they occur.

Information That Is Collected

The Apple Software Update server collects the following information from client Software Update servers:

- Language
- Type
- Browser

Tools for Managing Software Update

The Workgroup Manager and Server Admin applications provide a graphical interface for managing Software Update in Mac OS X Server. In addition, you can manage Software Update from the command line by using Terminal.

These applications are included with Mac OS X Server and can be installed on another computer with Mac OS X v10.6 or later, making that computer an administrator computer. For more information on setting up an administrator computer, see the server administration chapter of *Getting Started*.

Server Admin

Server Admin provides access to tools you use to set up, manage, and monitor Windows services and other services. You use Server Admin to:

- Set up Mac OS X Server as a Software Update server. For instructions, see Chapter 8, “Setting Up Software Update.”
- Manage and monitor Software Update service. For instructions, see Chapter 4, “Setting Up Clients to Use NetBoot and NetInstall Images.”

For more information about using Server Admin, see *Advanced Server Administration*. This includes information about:

- Opening and authenticating in Server Admin
- Working with specific servers
- Administering services
- Using SSL for remote server administration
- Customizing the Server Admin environment

Server Admin is installed in `/Applications/Server/`.

Workgroup Manager

Workgroup Manager provides comprehensive management of clients of Mac OS X Server. You use Workgroup Manager to set preferences by user, group, or computer to access your Software Update server. For more information about how to configure managed preferences for the Software Update server, see *User Management*.

For basic information about using Workgroup Manager, see *User Management*. This includes:

- Opening and authenticating in Workgroup Manager
- Administering accounts
- Customizing the Workgroup Manager environment

Workgroup Manager is installed in `/Applications/Server/`.

Command-Line Tools

A full range of command-line tools is available for administrators who prefer to use command-driven server administration. For remote server management, submit commands in a secure shell (SSH) session. You can enter commands on Mac OS X servers and computers using the Terminal application, located in the `/Applications/Utilities/` folder.

Setting Up Software Update

8

Use this chapter to set up Software Update on your network for Mac OS X v10.6 clients.

You use Software Update in Server Admin to provide local software updates to client computers.

Setup Overview

Here is an overview of the basic steps for configuring your Software Update server. This includes setting up Software Update service, configuring client computer access to the server, and testing.

Step 1: Evaluate and update your network, servers, and client computers as necessary. The number of client computers you can support using Software Update is determined by the number of servers you have, how they're configured, hard disk storage capacity, and other factors. See "Capacity Planning" on page 83.

Depending on the results of this evaluation, you might want to add servers or hard disks, add Ethernet ports, or make other changes to your servers.

For your client computers to use the local Software Update service, you must update them to Mac OS X v10.4 or later.

Step 2: Create your Software Update service plan. Decide which users will access Software Update.

You might have groups who need unlimited access while others might need a more limited choice of software updates. Such a plan requires more than one Software Update server with client computers bound using directory services to manage user preferences.

Step 3: Configure the Software Update server. Decide how you want to copy and enable software updates from Apple: automatically or manually. Set the maximum bandwidth you want a single computer to use when downloading update packages from your server. See "Setting Up Software Update" on page 85.

Step 4: Start Software Update. Your server synchronizes with the Apple Software Update server by requesting a catalog of available updates. If you chose to automatically copy updates, your server will begin to download all available software update packages. See “Starting Software Update” on page 87.

Step 5: (Optional) Manually copy and enable selected packages. If you do not choose to automatically copy and enable all Apple software updates, you must manually select software update packages to copy and enable. See “Copying and Enabling Selected Updates from Apple” on page 91.

Step 6: Set up client computers to use the correct Software Update server. Set preferences in Workgroup Manager by user, group, or computer to access your Software Update server. For more information about how to configure managed preferences for the Software Update server, see *User Management*.

Step 7: Test your Software Update server setup. Test Software Update by requesting software updates from the server using a client bound to preferences you set in Workgroup Manager. Make sure the packages are accessible to your users.

Considerations and Requirements

Before you set up a Software Update server, review the following hardware and network considerations and requirements.

What You Must Know

Before you set up Software Update on your server, you must be familiar with your network configuration and you must meet the following requirements:

- You’re the server administrator.
- You’re familiar with network setup.

You might also need to work with your networking staff to change network topologies, switches, routers, and other network settings.

Client Computer Requirements

Macintosh computers running Mac OS X v10.4 or later that are networked to a server running Mac OS X Server v10.4 or later can use Software Update to update Apple software.

Network Hardware Requirements

The type of network connections to use depends on the number of clients you expect to serve software updates to:

- To provide regular updates to fewer than 10 clients, use 100-Mbit Ethernet.
- To provide regular updates to 10–50 clients, use 100-Mbit switched Ethernet.
- To provide regular updates to more than 50 clients, use Gigabit Ethernet.

These are estimates for the number of clients supported. For more details about the optimal system and network configurations to support the number of clients you have, see “Capacity Planning” on page 83.

Note: In Mac OS X Server, Software Update operates across all network interfaces that TCP/IP is configured for.

Capacity Planning

The number of client computers your server can support when accessing Software Update depends on how your server is configured, when and how often your clients check for updates, the size of the updates, and a number of other factors.

When planning for your server and network needs, consider these main factors:

- **Ethernet speed:** 100Base-T or faster connections are required for client computers and the server. As you add clients, you might need to increase the speed of the Ethernet connections of your server.

Ideally you want to take advantage of the Gigabit Ethernet capacity built in to your Mac OS X server hardware to connect to a Gigabit switch. From the switch, connect Gigabit Ethernet or 100-Mbit Ethernet to each Macintosh client.

- **Hard disk capacity and number of packages:** Software Update packages can occupy considerable hard disk space on server volumes, depending on the size and configuration of the package and the number of packages being stored.
- **Number of Ethernet ports on the switch:** Distributing Macintosh clients over multiple Ethernet ports on your switch offers a performance advantage. Each port must serve a distinct segment.
- **Number of Software Update servers on the network:** You might want to provide different software updates to various groups of users. By configuring directory services you can offer different update services by network or hardware type, each targeting a different Software Update server on the network.

Note: You can't configure Software Update servers to talk to one another.

Before Setting Up Software Update

Before you set up Software Update, consider the following topics.

Consider Which Software Update Packages to Offer

Before you set up Software Update, consider whether to provide all or only part of Apple's software updates. Your client computers might run application software that requires a specific version of Apple software for the application to operate correctly.

You can configure your Software Update server to serve only Software Update packages you approve. Restricting access to update packages might help prevent maintenance and compatibility problems with your computers.

You can restrict client access in a Software Update server by disabling automatic mirror-and-enable functions in the General Settings pane. You manage specific updates in the Updates pane of the Software Update server.

Software Update Storage

Software updates can easily take a large amount of disk space over time and cause problems with system resources. In a production environment, it is important to prevent the system disk from becoming full and causing instability.

To eliminate the possibility of software updates filling a volume, system administrators normally limit the type of data being stored on the root partition and place data that could grow substantially in size on other partitions. For example, you could use an Xserve RAID to store software updates.

By default, software updates are stored in the `var/db/swupd/` folder. To store software updates in another location, choose a different partition or volume in the Software Update General settings pane.

To modify existing Software Update storage:

- 1 Open Server Admin and connect to the server.
- 2 Click the triangle at the left of the server.
The list of services appears.
- 3 From the expanded Servers list, select Software Update.
- 4 If Software Update is started, click the Stop Software Update button.
- 5 Click General.
- 6 Click Choose, and select the location where you want to store downloaded software updates.
- 7 Click Save.
- 8 (Optionally) If software updates were previously downloaded, use Terminal to copy the default software update folder to the new location:

```
$ sudo cp -p /private/var/db/swupd/html /Volumes/My_Volume/My_Software_Updates_Folder/
```

- 9 Click the Start Software Update button to confirm correct operation.
- 10 (Optionally) Use Terminal to delete the previous storage location to reclaim startup volume space:

```
$ sudo rm -rf /private/var/db/swupd/html
```

Organize Your Enterprise Client Computers

You might have individuals, groups, or groups of computers with common needs for only a few software update packages, while others might need unrestricted access to all software updates.

To provide varied access to software update packages, you must set up multiple Software Update servers. Use managed preferences to configure these computers to access a specific Software Update server.

For more information about how to configure managed preferences for the Software Update server, see *User Management*.

Turning Software Update On

Before you can configure Software Update settings, you must turn on Software Update in Server Admin.

To turn Software Update on:

- 1 Open Server Admin and connect to the server.
- 2 Click Settings.
- 3 Click Services.
- 4 Click the Software Update checkbox.
- 5 Click Save.

Setting Up Software Update

You set up Software Update by configuring the following groups of settings on the Settings pane for Software Update in Server Admin.

- **General.** This sets information about automatically copying and enabling updates, purging obsolete updates, and limiting user bandwidth.
- **Updates.** This lists available updates and provides date, name, version, and size information for each.

The following sections describe the tasks for configuring these settings and how to start Software Update after you configure it.

Configuring Software Update General Settings

You can use the General settings to set system update copy and enable settings, to remove obsolete updates, and to limit user bandwidth.

To configure Software Update General settings:

- 1 Open Server Admin and connect to the server.
- 2 Click the triangle at the left of the server.
The list of services appears.
- 3 From the expanded Servers list, select Software Update.
- 4 Click Settings.

- 5 To limit client user bandwidth, select “Limit user bandwidth for updates to” and enter the maximum rate of update bandwidth per user.
From the pop-up menu, choose KB/second or MB/second.
- 6 Click Choose, and select where the Software Update catalog and downloads will be stored. The default location is `/var/db/swupd/`.
- 7 To specify a port that software updates are provided through, enter a port number in the “Provide updates using port” field.
- 8 To keep a copy of the software updates on your server, select “Copy ___ updates from Apple” and choose from the following options.
 - If you want all updates copied from the Apple update server, choose “all” in the pop-up menu.
 - If you want only new updates copied from the Apple update server, choose “all new” in the pop-up menu.
- 9 To immediately enable all software updates for client users, select “Automatically enable copied updates.”

Enabling this feature retrieves all Apple published catalog updates and disables deprecated software packages which have a replacement package available. An administrator can choose to disable the new software package and continue offering the deprecated package.

If this feature is not selected and an administrator manually enables updates, disabling of deprecated software packages is performed on an individual product basis as replacement packages are enabled.
- 10 Click Save.

Configuring Updates Settings

You can use Updates settings to refresh the software update catalog, to copy and enable individual updates, and to view specific update information.

Downloading Apple updates disables deprecated software packages which have a replacement package available. An administrator can choose to disable the new software package and continue offering the deprecated package.

To configure Updates settings:

- 1 Open Server Admin and connect to the server.
- 2 Click the triangle at the left of the server.
The list of services appears.
- 3 From the expanded Servers list, select Software Update.
- 4 Click Updates.
- 5 Click the Refresh button to synchronize with the Apple server.

An unscheduled synchronization does not change or delay the next scheduled synchronization operation, which occurs every 24 hours.

- 6 Click Copy Now to copy software updates to your server.
- 7 Select the checkbox in the Enable column for each update that you want to make available to client computers.

The Enable column is disabled if the “Automatically enable copied updates” checkbox is selected. To manually enable or disable updates, deselect this checkbox in the Settings pane.

- 8 Click Save.

Starting Software Update

Use Server Admin to start Software Update.

To start Software Update:

- 1 Open Server Admin and connect to the server.
- 2 Click the triangle at the left of the server.
The list of services appears.
- 3 From the expanded Servers list, select Software Update.
- 4 Click the Start Software Update button (below the Servers list).

Pointing Unmanaged Clients to a Software Update Server

If you are not using Client Management, use the `defaults` command in Terminal to point unmanaged client computers to a Software Update server. You must be an administrator user to use the `defaults` command.

To point unmanaged clients to a software update server:

- 1 On the unmanaged client, open Terminal.
- 2 Enter the following command:

```
$ defaults write /Library/Preferences/com.apple.SoftwareUpdate CatalogURL  
URL
```

Replace *URL* with the URL of the Software Update server for the, including the port number and the name of catalog file for the specific version of Mac OS X. For example:

- For Mac OS Xv10.4:
`http://su.domain_name.com:8088/index.sucatalog`
- For Mac OS X v10.5:
`http://su.domain_name.com:8088/index-leopard.merged-1.sucatalog`
- For Mac OS X v10.6:
`http://su.domain_name.com:8088/index-leopard-snowleopard.merged-1.sucatalog`

You can verify your change using the following command:

```
$ defaults read /Library/Preferences/com.apple.SoftwareUpdate CatalogURL
```

To point the unmanaged client computer back to the Apple Software Update server, use the following command:

```
$ defaults delete /Library/Preferences/com.apple.SoftwareUpdate  
    CatalogURL
```

Managing Software Update

9

Use this chapter to perform day-to-day management tasks for a Software Update server after the server is configured and running.

The following sections show how to manually refresh the updates catalog from the Apple server, check the status of Software Update, stop the service, and control the software updates cataloged and distributed by the service.

Manually Refreshing the Updates Catalog from the Apple Server

Use Server Admin to manually update the updates catalog.

Note: Downloading Apple updates disables deprecated software packages which have a replacement package available. An administrator can choose to disable the new software package and continue offering the deprecated package.

To manually refresh the updates catalog from the Apple server:

- 1 Open Server Admin and connect to the server.
- 2 Click the triangle at the left of the server.
The list of services appears.
- 3 From the expanded Servers list, select Software Update.
- 4 Click Updates.
- 5 Click the Refresh button.

Checking the Status of Software Update

Use Server Admin to check the status of Software Update.

To check Software Update status:

- 1 Open Server Admin and connect to the server.

- 2 Click the triangle at the left of the server.
The list of services appears.
- 3 From the expanded Servers list, select Software Update.
- 4 To see whether the service is running, when it started, when it last checked for updates, the number of updates that are copied or enabled, and whether auto-copy and auto-enable are turned on, click Overview.
- 5 To review the Software Update service log, click Log.

Stopping Software Update

Use Server Admin to stop Software Update.

To stop Software Update:

- 1 Open Server Admin and connect to the server.
- 2 Click the triangle at the left of the server.
The list of services appears.
- 3 From the expanded Servers list, select Software Update.
- 4 Click the Stop Software Update button (below the Servers list).

Limiting User Bandwidth for Software Update

Use Server Admin to limit user bandwidth.

To limit user bandwidth for Software Update:

- 1 Open Server Admin and connect to the server.
- 2 Click the triangle at the left of the server.
The list of services appears.
- 3 From the expanded Servers list, select Software Update.
- 4 Click General.
- 5 Select "Limit user bandwidth for updates to."
- 6 Enter the maximum rate of update bandwidth per user.
- 7 From the pop-up menu, choose KB/second or MB/second.
- 8 Click Save.

Automatically Copying and Enabling Updates from Apple

Use Server Admin to copy and enable software updates automatically from Apple.

Enabling this feature retrieves all Apple published catalog updates and disables deprecated software packages which have a replacement package available. An administrator can choose to disable the new software package and continue offering the deprecated package.

If this feature is not selected and an administrator manually enables updates, disabling of deprecated software packages is performed on an individual product basis as replacement packages are enabled.

To automatically copy software updates and enable them for download:

- 1 Open Server Admin and connect to the server.
- 2 Click the triangle at the left of the server.
The list of services appears.
- 3 From the expanded Servers list, select Software Update.
- 4 Click General.
- 5 Select “Copy ___ updates from Apple” and choose one of the following options from the pop-up menu:
 - If you want all updates copied from the Apple update server, choose “all.”
 - If you want only new updates copied from the Apple update server, choose “all new.”
- 6 Select “Automatically enable copied updates.”
- 7 Click Save.

Copying and Enabling Selected Updates from Apple

Use Server Admin to copy selected software updates automatically from Apple.

Downloading Apple updates disables deprecated software packages which have a replacement package available. An administrator can choose to disable the new software package and continue offering the deprecated package.

To copy selected software updates and enable them for download:

- 1 Open Server Admin and connect to the server.
- 2 Click the triangle at the left of the server.
The list of services appears.
- 3 From the expanded Servers list, select Software Update.
- 4 Click General.
- 5 Make sure “Copy ___ updates from Apple” is deselected.
- 6 Make sure “Automatically enable copied updates” is deselected.
- 7 Click Save.

- 8 Click Updates.
- 9 Click Copy Now to copy software updates to your server.
This copies software updates to your server.
- 10 To enable individual software updates, select the checkbox in the Enable column of the update.
- 11 Click Save.

Removing Updates from a Software Update Server

When your local Software Update server downloads updates from Apple Software Update servers, the update packages remain on the local Software Update server until you delete them. These instructions describe how to manually delete updates.

To remove a specific software update:

- 1 On the local Software Update server, open Terminal and enter the following command to list the folders that correspond to each software update:

```
$ grep swupd /etc/swupd/com.apple.server.swupdate.plist > ~/Desktop/  
update_list.txt
```

This creates a file on your Desktop named `update_list.txt`. The file contains a list of software updates stored on the server.

- 2 Open the `update_list.txt` file.

This file contains information similar to the following:

```
<string>/usr/share/swupd/html/061-2036/.../SecUpd2005-007Ri.tar</string>  
<string>/usr/share/swupd/html/061-2048/.../SafariUpdate-2.0.1.tar</  
string>
```

Each update resides in a folder. In this example, the folder `/061-2048/` stores the Safari 2.0.1 update.

- 3 In Terminal, enter the following command to delete a software update from the server:

```
$ sudo rm -rf /usr/share/swupd/html/updatefolder/
```

Replace *updatefolder* with the name of the folder that stores the software update you want to delete.

For example, to remove the Safari 2.0.1 update, you would enter the following command:

```
$ sudo rm -rf /usr/share/swupd/html/061-2048/
```

- 4 When prompted, enter your administrator password.

Identifying Individual Software Update Files

Software updates are stored in the `/usr/share/swupd/html/` folder. Sometimes you might want to locate a specific software update file. Each software update that is copied to the server is stored with product ID numbers for a file name.

To make sure that you are selecting the correct software update file, correlate the file name (product ID) with the software update product ID in Server Admin. Each software update lists their product ID below the description field in the Updates Settings pane of Server Admin.

To view the product ID number of a software update:

- 1 Open Server Admin and connect to the server.
- 2 Click the triangle at the left of the server.
The list of services appears.
- 3 From the expanded Servers list, select Software Update.
- 4 Click Updates.
- 5 Select the software update from the list.

The software update product ID is displayed below the description field.

Use this chapter to find solutions for common problems you might encounter while working with Software Update.

This section contains solutions to common Software Update problems.

General Tips

- Make sure required services are installed.
- Make sure the Software Update packages you enable are meant for the client accessing them.
- If you detect poor response from the Software Update server, check the network load. For more information, see “Capacity Planning” on page 83.
- Delete old updates to make space for new ones.

If a Client Computer Can't Access the Software Update Server

- Make sure the client can access the network.
- Make sure the client's Software Update managed preference points to the Software Update server.
- Make sure the Software Update server is running.

If the Software Update Server Won't Sync with the Apple Server

Make sure the Apple server is accessible.

If Update Packages That the Software Update Server Lists Aren't Visible to Client Computers

Make sure the packages are enabled in Server Admin.

Command-Line Parameters

NetBoot Service Settings

To configure general NetBoot service setting from Terminal, use the following parameters with the `serveradmin` tool.

Parameter (netboot:)	Description
<code>filterEnabled</code>	A parameter that specifies whether client filtering is enabled. Default = "no"
<code>netBootStorageRecordsArray...</code>	An array of values for each server volume used to store boot or installation images. For a description, see "The Storage Record Array" on page 95.
<code>netBootFiltersRecordsArray...</code>	An array of values for each computer explicitly allowed or disallowed access to images. For a description, see "The Filters Record Array" on page 96.
<code>netBootImagesRecordsArray...</code>	An array of values for each boot or installation image stored on the server. For a description, see "The Image Record Array" on page 96.
<code>netBootPortsRecordsArray...</code>	An array of values for each server network port used to deliver boot or installation images. For a description, see "The Port Record Array" on page 97.

The Storage Record Array

An array of the following values appears in NetBoot service settings for each volume on the server used to store boot or installation images.

Parameter (netboot:)	Description
netBootStorageRecordsArray:_array_ index:<n>:sharepoint	The first parameter in an array describing a volume available to serve images. Default = "no"
netBootStorageRecordsArray:_array_ index:<n>:clients	Default = "no"
netBootStorageRecordsArray:_array_ index:<n>:ignorePrivs	Default = "false"
netBootStorageRecordsArray:_array_ index:<n>:volType	Default = <voltype> Example: "hfs"
netBootStorageRecordsArray:_array_ index:<n>:path	Default = "/"
netBootStorageRecordsArray:_array_ index:<n>:volName	Default = <name>
netBootStorageRecordsArray:_array_ index:<n>:volIcon	Default = <icon>
netBootStorageRecordsArray:_array_ index:<n>:okToDeleteClients	Default = "yes"
netBootStorageRecordsArray:_array_ index:<n>:okToDeleteSharepoint	Default = "yes"

The Filters Record Array

An array of the following values appears in NetBoot service settings for each computer explicitly allowed or denied access to images stored on the server.

Parameter (netboot:)	Description
netBootFiltersRecordsArray:_array_ index:<n>:hostName	The host name of the filtered computer, if available.
netBootFiltersRecordsArray:_array_ index:<n>:filterType	Whether the specified computer is allowed or denied access. Options: "allow" "deny"
netBootFiltersRecordsArray:_array_ index:<n>:hardwareAddress	The Ethernet hardware (MAC) address of the filtered computer.

The Image Record Array

An array of the following values appears in NetBoot service settings for each image stored on the server.

Parameter (netboot:)	Description
<code>netBootImagesRecordsArray:_array_ index:<n>:Name</code>	The name of the image as it appears in the Startup Disk control panel (Mac OS 9) or Preferences pane (Mac OS X).
<code>netBootImagesRecordsArray:_array_ index:<n>:IsDefault</code>	yes Specifies this image file as the default boot image on the subnet.
<code>netBootImagesRecordsArray:_array_ index:<n>:RootPath</code>	The path to the .dmg file.
<code>netBootImagesRecordsArray:_array_ index:<n>:isEdited</code>	Whether the image is edited.
<code>netBootImagesRecordsArray:_array_ index:<n>:BootFile</code>	Name of the boot ROM file: <code>booter</code> .
<code>netBootImagesRecordsArray:_array_ index:<n>:Description</code>	Arbitrary text describing the image.
<code>netBootImagesRecordsArray:_array_ index:<n>:SupportsDiskless</code>	yes Directs the NetBoot server to allocate space for shadow files needed by diskless clients.
<code>netBootImagesRecordsArray:_array_ index:<n>:Type</code>	NFS or HTTP.
<code>netBootImagesRecordsArray:_array_ index:<n>:pathToImage</code>	The path to the parameter list file in the .nbi folder on the server describing the image.
<code>netBootImagesRecordsArray:_array_ index:<n>:Index</code>	1-4095 Indicates a local image unique to the server. 4096-65535 is a duplicate, identical image stored on multiple servers for load balancing.
<code>netBootImagesRecordsArray:_array_ index:<n>:IsEnabled</code>	Sets whether the image is available to NetBoot (or Network Image) clients.
<code>netBootImagesRecordsArray:_array_ index:<n>:IsInstall</code>	yes Specifies a network installation image. no Specifies a NetBoot image.

The Port Record Array

An array of the following items is included in the NetBoot service settings for each network port on the server set to deliver images.

Parameter (netboot:)	Description
<code>netBootPortsRecordsArray:_array_ index:<m>:isEnabledAtIndex</code>	The first parameter in an array describing a network interface available for responding to netboot requests. Default = "no"
<code>netBootPortsRecordsArray:_array_ index:<m>:nameAtIndex</code>	Default = "<devname>" Example: "Built-in Ethernet"
<code>netBootPortsRecordsArray:_array_ index:<m>:deviceAtIndex</code>	Default = "<dev>" Example: "en0"

Index

A

access

- client management 60, 81, 83
- load balancing 69
- path for client 22
- restricting NetBoot 37, 49, 58
- restricting Software Update 76, 84

Add Packages and Post-Install Scripts action 34

Add User Account action 35

AFP (Apple Filing Protocol) service 46

AirPort wireless network 46

Apple Filing Protocol service. *See* AFP

Apply System Configuration Settings action 35

Architectures property 20

ASR (Apple Software Restore) 29

asr tool 29, 30, 61

Automator actions

- Add Packages and Post-Install Scripts 34
- Add User Account 35
- Apply System Configuration Settings 35
- Create Image 36
- Customize Package Selection 33
- Define Image Source 34
- Enable Automated Installation 36
- Filter Clients by MAC Address 37
- Filter Computer Model 37
- overview 33
- Partition Disk 38

B

bandwidth limitations for Software Update 78, 90

boot image, definition 16

- See also* NetBoot service

Boot Server Discovery Protocol. *See* BSDP

BootFile property 20

BootP (Bootstrap Protocol) 21, 62

Bootstrap Protocol. *See* BootP

BSDP (Boot Server Discovery Protocol) 21, 59

C

client computers

- diskless startup 54, 56, 57, 60
- hardware requirements 45

NetBoot 30

- network requirements 45
- setup 60, 62
- shadow files 54, 63, 70
- troubleshooting NetBoot startup 71

See also Automator actions, Software Update service

clients

- capacity planning 46
- diskless startup 71
- groups 17, 81, 83, 84
- imaging multiple 61
- NetBoot 18, 19, 22
- viewing lists of 65, 66

command-line tools

- assembling workflows 40
- creating images 32
- disabling images 65
- enabling images 52, 58
- logs 67
- NetBoot settings 25, 95, 96, 97
- package-making 41, 42
- restoring images 30
- service settings 50
- Software Update service 80
- starting NetBoot 51
- startup image selection 61
- status checking 66
- stopping service 65
- storing image files 53, 54

computer name 36

configuration, client settings 35

Create Image action 36

Customize Package Selection action 33

D

Define Image Source action 34

Description property 21

DHCP (Dynamic Host Configuration Protocol)

- service 21, 44, 46, 51, 71

disk images. *See* NetBoot service, NetInstall

diskless startup 54, 56, 57, 60, 71

disks

- capacity planning 38, 46, 83
- distribution of images across 68
- partitions 38

documentation 11, 12

drives. *See* disks

Dynamic Host Configuration Protocol. *See* DHCP

E

Enable Automated Installation Action 36

Ethernet 45, 46, 83

F

file services 46

- See also* share points

files

- boot 22
- Software Update storage 84

Filter Clients by MAC Address action 37

Filter Computer Model action 37

filters record array, NetBoot 96

filters, NetBoot 49, 58

folders, NetBoot image 19

G

groups, setup 17, 81, 83, 84

H

hardware requirements 45, 82

hdiutil tool 32

help, using 10

host name, local 36

HTTP (Hypertext Transfer Protocol) 46

I

image record array, NetBoot 96

images. *See* NetBoot service, NetInstall

Index property, NetBoot image 20

installation image, definition 16

- See also* NetInstall

IsDefault property 21

IsEnabled property 21

IsInstall property 21

L

Language property 21

load balancing 19, 67, 68, 69, 70

logs 50, 67, 79

M

MAC address 37, 49, 58

memory, requirements for 45

multicast 61

N

N key startup procedure 62

Name property 21

naming conventions 52, 72

NetBoot service

- adding packages to images 41, 42
- boot file management 22
- capacity planning 46
- client setup 45, 60
- creating images 26, 27, 29, 30
- default settings 56
- disabling images 65
- enabling images 52
- filters 49, 58
- image folder 19
- management tools 23, 24, 25, 52
- monitoring of 64, 65, 66, 67, 68, 69, 70
- NetBoot 1.0 support 50
- network service requirements 46
- overview 9, 16, 17, 18, 19
- prerequisites 44, 45
- property list file 20
- security 22
- selecting boot image 60
- server discovery 21, 59
- settings 48, 95, 96, 97
- setup 35, 43, 48
- starting 47, 51
- status checking 66
- stopping 64
- storage for images 22, 52, 54, 55
- testing 44
- troubleshooting 71, 72
- updating images 32
- viewing client lists 65, 66
- workflows 33, 34, 35, 36, 37, 38, 39
- See also* Automator actions

NetBootClientsn share points 19, 63, 70

NetBootSPn 18, 22

NetInstall

- adding software to images 41, 42
- creating images 26, 28, 30
- overview 9, 16, 18, 23
- selecting install image 62
- using stored images 22
- workflows 33, 34, 35, 36, 37, 38, 39
- See also* Automator actions

NetRestore 29

Network File System. *See* NFS

network requirements 45, 46, 82, 83

network services 21, 44, 46, 51, 71

NFS (Network File System) 46

P

package install images 33, 34, 41, 42

PackageMaker 17, 41, 42

packages, Software Update 77, 78, 83, 93

Partition Disk action 38

- port record array, NetBoot 97
- post-install scripts 34
- problems. *See* troubleshooting
- Property List Editor 17
- property list files 20
- protocols
 - AFP 46
 - BootP 21, 62
 - BSDP 21, 59
 - DHCP 21, 44, 46, 71
 - HTTP 46
 - TFTP 22, 46

R

- RAM (random-access memory) 45
- remote servers, images stored on 55
- RootPath property 21

S

- security 22
 - See also* access
- serial number, server 47
- Server Admin 17, 24, 79
- servers
 - discovery of 21, 59
 - images on remote 55
 - load balancing 67, 68, 69
 - NetBoot 18
 - Software Update 83, 87, 94
- setup procedures. *See* configuration, installation
- shadow files 18, 19, 54, 63, 70
- share points
 - NetBootClientsn 19, 63, 70
 - NetBootSPn 18, 22
 - shadow files 18, 19, 70
- software requirements 45, 81
- Software Update service
 - automatic settings 91
 - capacity planning 83
 - catalog management 77, 89
 - clients 76, 78, 82, 84, 87
 - file packages 77, 78, 83, 93
 - file storage 84
 - identifying files 93
 - limitations on bandwidth 78, 90
 - management tools 79, 80, 89
 - monitoring of 78, 79
 - overview 9, 76, 77
 - prerequisites 82
 - removing updates 92
 - settings 84, 85, 86
 - setup overview 81
 - starting 85, 87
 - status checking 89
 - stopping 90
 - troubleshooting 94

- startup. *See* NetBoot service
- storage record array, NetBoot 95
- streaming media, multicast 61
- subnets 59
- SupportsDiskless property 21
- System Image Utility
 - creating images 26
 - overview 9, 17, 20, 24
- system imaging. *See* NetBoot service, NetInstall
- systemsetup tool 61

T

- TFTP (Trivial File Transfer Protocol) 22, 46
- troubleshooting
 - NetBoot service 71, 72
 - Software Update service 94
- Type property 21

U

- updating disk images 45
 - See also* Software Update service
- user accounts, adding 35
 - See also* client computers
- users. *See* clients

V

- volumes, cloning 29

W

- workflows 33
 - adding 39
 - assembling 38, 39
 - Automator actions 33, 34, 35, 36, 37, 38
 - removing 39
- Workgroup Manager 24, 80
- workgroups 43